

# Product data sheet

Specifications



## APC Professional SurgeArrest, 8 outlet, phone line & coax protection

PRO8TV

⚠ Discontinued on: 10 June 2022

⚠ Discontinued

### Overview

Lead time	Usually in Stock
-----------	------------------

### Main

Main Input Voltage	120 V
Input Connection Type	NEMA 5-15P
Cable length	1.83 m
Number of cables	1
Provided equipment	2 x 1.8 m telephone cables 60 cm coaxial cable User manual

### Physical

Colour	Beige
Height	4.4 cm
Width	20.3 cm
Depth	14.6 cm
Net weight	1 kg
Mounting preference	No preference
Mounting mode	Not rack-mountable

### Input

Maximum line current	15 A
Network frequency	50/60 Hz +/- 5 Hz auto-sensing

### Output

Number of power socket outlets	8
Outlet standard	NEMA 5-15R

### Conformance

UL 1449 TVSS rating	330
---------------------	-----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Product certifications	CSA
Standards	UL 497B UL 1283 UL 1363 UL 1449
Equipment protection policy	Lifetime : \$75000

### Environmental

Ambient air temperature for operation	0...45 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

### Surge Protection and Filtering

EP joule rating	1760 J
Data line protected	1
Response time	0 ns common mode
Common mode rejection	60 dB
Peak current	13 kAcommon mode 13 kAnormal mode
Surge energy rate	320 J

### Packing Units

SCC14	10731304000836
-------	----------------

### Contractual warranty

Warranty	Limited Lifetime
----------	------------------

### Recommended replacement(s)