

# Product data sheet

Specifications



## APC Smart-UPS 250VA, 230V, rackmount, 1U, 4x IEC 60320 C13 & 2x IEC Jumpers outlets

PS250I

 **Discontinued on:** Jun 10, 2022

 **Discontinued**



### Overview

Lead Time Usually in Stock

### Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Rated Power In W	165 W
Rated Power In Va	250 VA
Input Connection Type	IEC 60320 C14
Nb Of Power Socket Outlets	4 IEC 60320 C13 2 IEC Jumpers
Number Of Rack Unit	1U
Number Of Cables	1
Battery Type	Lead-acid battery
Provided Equipment	User manual Rack mounting brackets Smart UPS signalling RS-232 cable CD with software

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a> 
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	5 h
Number Of Battery Replacement Quantity	1
Replacement Battery	<a href="#">RBC18</a> 

### Physical

Colour	Black
Height	4.4 cm
Width	44.5 cm
Depth	33 cm
Net Weight	8.18 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Mounting Location	Front
Mounting Preference	Lower
Mounting Mode	Rack-mounted
Two Post Mountable	0
Usb Compatible	No

## Input

Network Frequency	50/60 Hz +/- 3 Hz auto-sensing
Input Voltage Limits	151...302 V adjustable 160...286 V

## Output

Maximum Configurable Power In W	165 W
Ups Type	Line interactive

## Conformance

Product Certifications	C-Tick CE GOST VDE
Standards	EN 50091-1 EN 50091-2

## Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 %
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage Altitude	0.00...15240.00 m
Acoustic Level	38 dBA
Heat Dissipation	55 Btu/h

## Communications & Management

Free Slots	0
Control Panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm
Emergency Power Off	Optional

## Surge Protection and Filtering

Surge Energy Rate	320 J
Noise Suppression	Full time multi-pole noise filtering : 0.7% IEEE surge let-through : zero clamping response time : meets UL 1449

## Packing Units

Package 1 Weight	10.68 kg
Package 1 Height	15.9 cm
Package 1 Width	57.8 cm
Package 1 Length	44.5 cm
Number Of Units In Package 3	24

## Contractual warranty

Warranty	2 years repair or replace, optional on-site warranties available, optional extended warranties available
----------	--