

SL10KF
DISCONTINUED

 [Email Technical Specifications](#)

 [Printer Friendly](#)

Be the first to [write a review](#)

[+ More Images](#)

Ratings and Reviews

Output Power Capacity	10 kW / 10 kVA
Max Configurable Power	10 kW / 10 kVA
Nominal Output Voltage	120V,208V,208V 3PH
Output Voltage Note	Configurable for 200 : 208 or 220V 3 Phase nominal output voltage
Efficiency at Full Load	93.6%
Output Voltage Distortion	Less than 3%
Output Frequency (sync to mains)	50 Hz - programmable +/- 0.5 / 1 / 2 / 4 / 6 / 8%,60 Hz - programmable +/- 0.5 / 1 / 2 / 4 / 6 / 8%
Crest Factor	Unlimited
Waveform Type	Sine wave
Output Connections	(1) Hard Wire 5-wire (3PH + N + G) (1) Screw Terminals
Bypass	Built-in Static Bypass

Nominal Input Voltage	208V 3PH
Input Frequency	50 Hz - programmable +/- 0.5 / 1 / 2 / 4 / 6 / 8%, 60 Hz - programmable +/- 0.5 / 1 / 2 / 4 / 6 / 8%
Input Connections	Hard Wire 5-wire (3PH + N + G)
Input voltage range for main operations	170 - 230 (200V), 177 - 239 (208V), 187 - 242 (220V)V

Battery Type	No internal battery - uses external battery system
Replacement battery cartridge note	A Battery Breaker Box is required for all 10kW External Battery Solutions.

Interface Port(s)	Contact Closure,DB-25 RS-232
Available SmartSlot™ Interface Quantity	2
Pre-Installed SmartSlot™ Cards	AP9617
Control panel	Multi-function LCD status and control console
Audible Alarm	Beep for each 52 alarm conditions
Emergency Power Off (EPO)	Yes

Maximum Height	1400.00 mm
Maximum Width	600.00 mm
Maximum Depth	800.00 mm
Net Weight	190.91 KG
Shipping Weight	213.64 KG
Shipping Height	1700.00 mm
Shipping Width	700.00 mm
Shipping Depth	900.00 mm
Color	Dark green (NCS 7020 B50G),Light grey (NCS 2703-G84Y)
Units per Pallet	1.00

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-999.9 meters
Storage Temperature	-50 - 40 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	55.00 dBA
Online Thermal Dissipation	2388.00 BTU/hr
Protection Class	NEMA 1 with NEMA 12 optional

Regulatory Approvals	cUL Listed,FCC Part 15 Class A,ISO 14001,ISO 9001,UL 1778,UL Listed
Standard Warranty	1 year (parts only),optional on-site warranties available,optional extended warranties available