

SL20KG
DISCONTINUED

 [Email Technical Specifications](#) [Printer Friendly](#)Be the first to [write a review](#)

[+ More Images](#)

Ratings and Reviews

Output Power Capacity	20 kW / 20 kVA
Max Configurable Power	20 kW / 20 kVA
Nominal Output Voltage	480V 3PH
Efficiency at Full Load	94.9%
Output Voltage Distortion	Less than 3%
Output Frequency (sync to mains)	60 Hz - programmable +/- 0.5 / 1 / 2 / 4 / 6 / 8%
Crest Factor	Unlimited
Waveform Type	Sine wave
Output Connections	(1) Hard Wire 4-wire (3PH + G)
Bypass	Built-in Static Bypass

Nominal Input Voltage	480V 3PH
Input Frequency	60 Hz - programmable +/- 0.5 / 1 / 2 / 4 / 6 / 8%
Input Connections	Hard Wire 4-wire (3PH + G)
Input voltage range for main operations	408 - 552 (480)V

Battery Type	No internal battery - uses external battery system
Replacement battery cartridge note	If longer runtimes are needed, please contact APC at 800-800-4272.

Interface Port(s)	Contact Closure,DB-25 RS-232
Available SmartSlot™ Interface Quantity	2
Pre-Installed SmartSlot™ Cards	AP9617
Control panel	Multi-function LCD status and control console
Audible Alarm	Beep for each 52 alarm conditions
Emergency Power Off (EPO)	Yes

Maximum Height	1400.00 mm
Maximum Width	600.00 mm
Maximum Depth	800.00 mm
Net Weight	275.00 KG
Shipping Weight	297.73 KG
Shipping Height	1700.00 mm
Shipping Width	700.00 mm
Shipping Depth	900.00 mm
Color	Dark green (NCS 7020 B50G),Light grey (NCS 2703-G84Y)
Units per Pallet	1.00

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-999.9 meters
Storage Temperature	-50 - 40 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters

Online Thermal Dissipation	3753.00 BTU/hr
----------------------------	----------------

Protection Class	NEMA 1 with NEMA 12 optional
------------------	------------------------------

Regulatory Approvals	FCC Part 15 Class A,ISO 9001,ISO 14001,UL 1778,UL Listed,cUL Listed
Standard Warranty	1 year repair or replace,optional on-site warranties available,optional extended warranties available