

Product data sheet

Specifications



APC Smart-UPS C, Line Interactive, 3kVA, Tower, 115V, 8x NBR 14136 outlets, USB and Serial communication, AVR, Graphic LCD

SMC3000XL-BR

⚠ To be discontinued

⚠ To be discontinued on: Jul 30, 2024

⚠ To be end-of-service on: Jun 30, 2026

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	115 V
Main Output Voltage	115 V
Rated power in W	3000 W
Rated power in VA	3000 VA
product or component type	Uninterruptible power supply (UPS)
Input Connection Type	NBR 14136
output connection type	8 NBR 14136
Cable length	1.8 m
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	User manual USB cable
Range of product	Smart-UPS BR

Batteries & Runtime

Run Time	View Runtime Graph
Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v
Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Number of battery replacement quantity	4
Battery life	1...2 year(s)
Battery charger power	108 W rated

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

General

Number of power module filled slots	0
Number of power module free slots	0
Redundant	No

Physical

Colour	Black
Height	49.3 cm
Width	20.5 cm
Depth	52.1 cm
net weight	52 kg
mounting location	Front
Mounting preference	No preference
mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Maximum input current	19 A
Switching current capacity	30 A
Input voltage limits	90...140 V
Input current	19 A (1 phase)
Network frequency	60 Hz

Output

Maximum configurable power in VA	3000 VA
Maximum configurable power in W	3000 W
UPS type	Line interactive
Wave type	Sine wave
Efficiency	92 % (full load)

Environmental

Acoustic level	50 dBA
----------------	--------

Communications & Management

control panel	LED status display with load and battery bar-graphs and on line : on battery : replace battery : and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	960 J
-------------------	-------

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	70.5 cm
Package 1 Width	62.1 cm
Package 1 Length	31.5 cm
Package 1 Weight	56 kg

Contractual warranty

Warranty	2 years repair or replace (excluding battery) and 1 year for battery
----------	--

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Eu Rohs Directive	Under investigation
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins