

Product data sheet

Specifications



APC Smart-UPS C, Line Interactive, 3kVA, Tower, 220V, 8x NBR 14136 outlets, USB and Serial communication, AVR, Graphic LCD

SMC3000XLI-BR


Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	220 V
Main Output Voltage	220 V
Rated power in W	3000 W
Rated power in VA	3000 VA
product or component type	Uninterruptible power supply (UPS)
Input Connection Type	NBR 14136
output connection type	8 NBR 14136
Output connector type	Hard wire 3-wire (H N + E) 1
Cable length	1.8 m
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	User manual USB cable

Batteries & Runtime

Run Time	View Runtime Graph 
Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several v
Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	8 h
Number of battery replacement quantity	4
Battery life	1...2 year(s)
Battery charger power	108 W rated

General

Number of power module filled slots	0
-------------------------------------	---

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of power module free slots	0
Redundant	No

Physical

Colour	Black
Height	49.3 cm
Width	20.5 cm
Depth	52.1 cm
net weight	52 kg
mounting location	Front
Mounting preference	No preference
mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Maximum input current	19 A
Switching current capacity	30 A
Input voltage limits	176...264 V
Input current	19 A (1 phase)
Network frequency	60 Hz

Output

Maximum configurable power in VA	3000 VA
Maximum configurable power in W	3000 W
UPS type	Line interactive
Wave type	Sine wave
Efficiency	92 % (full load)

Environmental

Acoustic level	50 dBA
----------------	--------

Communications & Management

control panel	LED status display with load and battery bar-graphs and on line : on battery : replace battery : and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	1650 J
-------------------	--------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Number of Units in Package 1	1
Package 1 Height	70.5 cm
Package 1 Width	62.1 cm
Package 1 Length	31.5 cm
Package 1 Weight	56 kg

Contractual warranty

Warranty	2 years repair or replace (excluding battery) and 1 year for battery
----------	--

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency

Eu Rohs Directive	Under investigation
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information