

Product data sheet

Specifications



APC Smart-UPS, Line Interactive, 1500VA, Rackmount 2U, 120V, 6x NEMA 5-15R outlets, SmartSlot, AVR, LCD, TAA, Not for sale in the US

SMT1500RMUS

⚠ Discontinued - Service only

⚠ Discontinued on: May 4, 2022

⚠ To be end-of-service on: May 5, 2024

Overview

Lead Time	Usually Ships within 2 Weeks
-----------	------------------------------

Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Rated Power In W	1000 W
Rated Power In Va	1440 VA
Input Connection Type	NEMA 5-15P
Nb Of Power Socket Outlets	6 NEMA 5-15R
Number Of Rack Unit	2U
Cable Length	2.44 m
Number Of Cables	1
Battery Type	Lead-acid battery
Provided Equipment	CD with software Documentation CD Installation guide Rack mounting support rails USB cable

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Extended Runtime	0
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	3 h
Number Of Battery Replacement Quantity	1
Battery Life	4...6 year(s)
Replacement Battery	APCRBC133

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Battery Power In Vah	432 VAh runtime
Battery Charger Power	144 W rated

General

Number Of Power Module Filled Slots	0
Number Of Power Module Free Slots	0
Product Web Sub-Family	TAA Compliant
Redundant	No

Physical

Colour	Black
Height	8.9 cm
Width	43.2 cm
Depth	45.7 cm
Net Weight	28.64 kg
Mounting Location	Front
Mounting Preference	Lower
Mounting Mode	Rack-mounted
Two Post Mountable	0
Usb Compatible	Yes

Input

Input Voltage Limits	75...154 V adjustable 82...144 V
Network Frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Harmonic Distortion	Less than 5 %
Maximum Configurable Power In Va	1440 VA
Maximum Configurable Power In W	1000 W
Transfer Time	4 ms typical : 8 ms maximum
Ups Type	Line interactive
Wave Type	Sine wave
Output Frequency	50/60 Hz +/- 3 Hz sync to mains

Conformance

Product Certifications	CSA TAA compliance
Equipment Protection Policy	Lifetime : \$150000
Standards	FCC part 15 class A UL 1778

Environmental

Acoustic Level	46 dBA
Heat Dissipation	90 Btu/h
Operating Altitude	0...10000 ft
Ambient Air Temperature For Operation	0...40 °C
Ambient Air Temperature For Storage	-15...45 °C
Storage Altitude	0.00...15240.00 m
Relative Humidity	0...95 %
Storage Relative Humidity	0...95 %

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Control Panel	Multifunction LCD status and control console
Emergency Power Off	Optional
Free Slots	1

Surge Protection and Filtering

Surge Energy Rate	459 J
Noise Suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Package 1 Height	25.1 cm
Package 1 Width	59.4 cm
Package 1 Length	60.3 cm
Package 1 Weight	31.91 kg
Number Of Units In Package 3	16

Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. **Green Premium** promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low- products. **Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile
California Proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Circularity Profile	End of Life Information