

Product data sheet

Specifications



APC Smart-UPS, Line Interactive, 3kVA, Tower, 230V, 6x IRAM+1x Hardwire (1P+N+E) outlets, SmartSlot, AVR, LCD

SMT3000I-AR

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Rated power in W	2700 W
Rated power in VA	3000 VA
product or component type	Uninterruptible power supply (UPS)
Input Connection Type	IEC 320 C20
output connection type	6 Argentinean
Output connector type	Hard wire 3-wire (H N + E) 1
Number of rack unit	0U
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	CD with software Documentation CD Smart UPS signalling RS-232 cable USB cable

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Extended runtime	1
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Battery life	3...5 year(s)
Replacement battery	RBC55
Battery charger power	271 W rated

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

General

Number of power module filled slots	0
Number of power module free slots	0
Redundant	No

Physical

Colour	Black
Height	43.5 cm
Width	19.7 cm
Depth	54.4 cm
net weight	52.5 kg
mounting location	Front
Mounting preference	No preference
mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes

Input

Input voltage limits	151...302 V adjustable 160...286 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Harmonic distortion	Less than 5 % at full load
Maximum configurable power in VA	3000 VA
Maximum configurable power in W	2700 W
Transfer time	2 ms typical
UPS type	Line interactive
Wave type	Sine wave
Output frequency	47...53 Hz for 50 Hz nominal sync to mains 57...63 Hz for 60 Hz nominal sync to mains

Conformance

Product certifications	CE CSA EAC RCM VDE
------------------------	--------------------------------

Environmental

Acoustic level	53 dBA
heat dissipation	375 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	0...40 °C

Ambient air temperature for storage	-15...45 °C
Storage altitude	0.0000000000...15240.0000000000 m
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %

Communications & Management

control panel	Multifunction LCD status and control console
Emergency power off	Yes
Free slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge energy rate	365 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	69.9 cm
Package 1 Width	76.2 cm
Package 1 Length	38.1 cm
Package 1 Weight	63.7 kg

Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery, optional on-site warranties available, optional extended warranties available
----------	--

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Transparency RoHS/REACH

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information