

SMV750I-GR

APC Easy UPS SMV 750VA, Schuko Outlet, 230V



Overview

Model Name	APC Easy UPS SMV 750VA, Schuko Outlet, 230V
Includes	Documentation CD , USB cable , User Manual
Standard Lead Time	Usually in Stock
Product Distribution	Algeria , Angola , Benin , Botswana , Burkina Faso , Cameroon , Central African Republic , Chad , Congo , CONGO, THE DEMOCRATIC REPUBLIC OF THE , Cote D'Ivoire , Cyprus , Equatorial Guinea , Gabon , Gambia , Ghana , Guadeloupe , Guinea , French Guiana , Indonesia , Iran (Islamic Republic Of) , Iraq , Jordan , Lebanon , Lesotho , Liberia , Madagascar , Malawi , Mali , Malta , Martinique , Mauritania , Mauritius , Mayotte , Mozambique , Namibia , Niger , Nigeria , Pakistan , Reunion , Senegal , Sierra Leone , South Africa , Sudan , Suriname , Thailand , Togo , Tunisia , Turkey , Turks And Caicos Islands , Viet Nam , Western Sahara , Zambia , Zimbabwe

Output

Output Power Capacity	525 Watts / 750 VA
Max Configurable Power (Watts)	525 Watts / 750 VA
Nominal Output Voltage	230V
Crest Factor	3 : 1
Crest Factor	Line Interactive
Waveform Type	Sine wave
Output Connections	(4) Schuko CEE 7 (Battery Backup)

Input

Nominal Input Voltage	230V
Input Frequency	45 - 65 Hz (auto sensing)
Input Connections	IEC-320 C14
Input voltage range for main operations	160 - 295 V
Other Input Voltages	220 , 240

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	4 hour(s)

Communications & Management

Interface Port(s)	USB
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Physical

Maximum Height	220.0 mm
Maximum Width	160.0 mm
Maximum Depth	410.0 mm
Net Weight	13.6 kg
Shipping Weight	16.61 kg
Shipping Height	339.0 mm
Shipping Width	272.0 mm
Shipping Depth	508.0 mm

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 90 %
Operating Elevation	0-999.9 meters
Storage Temperature	-10 - 40 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-3000 meters
Audible noise at 1 meter from surface of unit	45.000 dB

Conformance

Approvals	CE
Standard warranty	2 years repair or replace