

Product data sheet

Specifications



APC Smart-UPS X, Line Interactive, 1000VA, Rack/tower convertible 2U, 230V, 8x C13 IEC, SmartSlot, Extended runtime

SMX1000I

Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
--------------	---

Lead time	Usually Ships within 2 Weeks
-----------	------------------------------

Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Rated power in W	800 W
Rated power in VA	1000 VA
Input Connection Type	IEC 320 C14
Output connection type	8 IEC 320 C13 2 IEC Jumpers
Number of rack unit	2U
Cable length	1.83 m
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	CD with software Documentation CD Installation guide Rack mounting brackets Removable support feet Smart UPS signalling RS-232 cable USB cable

Batteries & Runtime

Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Overcurrent protection	60 A
Battery life	3...5 year(s)
Replacement battery	APCRBC116

Battery charger power	99 W rated
-----------------------	------------

General

Number of power module filled slots	0
-------------------------------------	---

Number of power module free slots	0
-----------------------------------	---

Product web sub-family	Extended run
------------------------	--------------

Redundant	No
-----------	----

Physical

Colour	Black
--------	-------

Height	8.9 cm
--------	--------

Width	43.2 cm
-------	---------

Depth	49 cm
-------	-------

Net weight	22.86 kg
------------	----------

Mounting preference	Lower
---------------------	-------

Mounting mode	Rack-mounted with kit
---------------	-----------------------

Two post mountable	1
--------------------	---

USB compatible	No
----------------	----

Input

Input voltage limits	151...302 V adjustable 160...286 V
----------------------	---------------------------------------

Network frequency	50/60 Hz +/- 3 Hz auto-sensing
-------------------	--------------------------------

Output

Harmonic distortion	Less than 5 %
---------------------	---------------

Maximum configurable power in VA	1000 VA
----------------------------------	---------

Maximum configurable power in W	800 W
---------------------------------	-------

UPS type	Line interactive
----------	------------------

Wave type	Sine wave
-----------	-----------

Output frequency	50/60 Hz +/- 3 Hz sync to mains
------------------	---------------------------------

Conformance

Product certifications	CE RCM VDE EAC
------------------------	-------------------------

Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
-----------	--

Environmental

Acoustic level	40 dBA
----------------	--------

Heat dissipation	82 Btu/h
------------------	----------

Operating altitude	0...10000 ft
--------------------	--------------

Ambient air temperature for operation	0...45 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 m
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %

Communications & Management

Control panel	Multifunction LCD status and control console
Emergency power off	Yes
Free slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	600 J
Noise suppression	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	24.6 cm
Package 1 Width	62 cm
Package 1 Length	58.9 cm
Package 1 Weight	27.32 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
RoHS exemption information	Yes
Circularity Profile	End of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---

Recommended replacement(s)