

# Product data sheet

Specifications



## APC Smart-UPS X 1500VA Rack/ Tower LCD 120V with Network Card TAA (Not for sale in CO, VT or WA)

SMX1500RMNCUS

⚠ Discontinued - Service only

⚠ Discontinued on: Jun 13, 2022

### Overview

Lead Time	Usually Ships within 2 Weeks
-----------	------------------------------


### Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Rated Power In W	1200 W
Rated Power In Va	1440 VA
Input Connection Type	NEMA 5-15P
Nb Of Power Socket Outlets	8 NEMA 5-15R
Number Of Rack Unit	2U
Cable Length	2.44 m
Number Of Cables	1
Battery Type	Lead-acid battery
Provided Equipment	CD with software Documentation CD Installation guide Rack mounting hardware Rack mounting support rails Removable support feet Smart UPS signalling RS-232 cable Temperature probe USB cable

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>
Extended Runtime	0
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	3 h
Number Of Battery Replacement Quantity	1
Overcurrent Protection	60 A
Battery Life	3...5 year(s)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Replacement Battery	<a href="#">APCRBC115</a> 
Battery Power In Vah	311 VAh runtime
Battery Charger Power	103 W rated
Battery Option	SMX48RMBP2U 1 933 VAh SMX48RMBP2U 2 1555 VAh SMX48RMBP2U 3 2077 VAh SMX48RMBP2U 4 2800 VAh SMX48RMBP2U 5 3421 VAh

## General

Number Of Power Module Filled Slots	0
Number Of Power Module Free Slots	0
Product Web Sub-Family	TAA Compliant
Redundant	No

## Physical

Colour	Black
Height	8.9 cm
Width	43.2 cm
Depth	49 cm
Net Weight	24.82 kg
Mounting Location	Front
Mounting Preference	Lower
Mounting Mode	Rack-mounted
Two Post Mountable	0
Usb Compatible	Yes

## Input

Maximum Input Current	12 A
Max Short Time Withstand Current	1000 kA
Switching Current Capacity	20 A
Input Voltage Limits	75...154 V adjustable 82...143 V
Network Frequency	50/60 Hz +/- 3 Hz auto-sensing

## Output

Harmonic Distortion	Less than 5 %
Maximum Configurable Power In Va	1440 VA
Maximum Configurable Power In W	1200 W
Ups Type	Line interactive
Wave Type	Sine wave
Output Frequency	50/60 Hz +/- 3 Hz sync to mains

## Conformance

Product Certifications	cUL listed TAA compliance
Equipment Protection Policy	Lifetime : \$150000
Standards	UL 1778

## Environmental

Acoustic Level	40 dBA
Heat Dissipation	133 Btu/h
Operating Altitude	0...10000 ft
Ambient Air Temperature For Operation	0...40 °C
Ambient Air Temperature For Storage	-15...45 °C
Storage Altitude	0.00...15240.00 m
Relative Humidity	0...95 %
Storage Relative Humidity	0...95 %

## Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Control Panel	Multifunction LCD status and control console
Preinstalled Device	Network management card 2 with environmental monitoring

## Surge Protection and Filtering

Surge Energy Rate	600 J
Noise Suppression	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449

## Packing Units

Package 1 Weight	30 kg
Package 1 Height	24.6 cm
Package 1 Width	58.9 cm
Package 1 Length	62 cm
Number Of Units In Package 3	8

## Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---

## Sustainability

**Green Premium™** label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. **Green Premium** promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low- products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)



Energy Efficient   Take-back   Transparency   RoHS/REACH

## Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

## Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information   [Yes](#)

## Certifications & Standards

Reach Regulation   [REACH Declaration](#)

Eu Rohs Directive   Compliant  
[EU RoHS Declaration](#)

Environmental Disclosure   [Product Environmental Profile](#)

Circularity Profile   [End of Life Information](#)