



Overview

Model Name	APC Smart-UPS 3000VA, 230V, Autonomia Estendida, Brazil
Includes	CD with software , Documentation CD , Door key , Rack Mounting brackets , Smart UPS signalling RS-232 cable , USB cable , User Manual
Standard Lead Time	Usually in Stock
Product Distribution	Brazil

Output

Output Power Capacity	2700 Watts / 3000 VA
Max Configurable Power (Watts)	2700 Watts / 3000 VA
Nominal Output Voltage	230V
Output Voltage Distortion	Less than 5%
Output Frequency (sync to mains)	47 - 53 Hz for 50 Hz nominal , 50/60Hz +/- 3 Hz
Other Output Voltages	208, 220, 240V
Crest Factor	3 : 1
Crest Factor	Line Interactive
Waveform Type	Sine wave
Output Connections	(9) NBR 14136 (Battery Backup)

Input

Nominal Input Voltage	208V , 230V
Input Frequency	50/60 Hz +/- 3 Hz (auto sensing)
Input Connections	NBR 14136
Cord Length	1,83 meters
Input voltage range for main operations	160 - 286 V
Other Input Voltages	220 , 240
Maximum Input Current	0 A
Input Breaker Capacity	0 A

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
--------------	--

Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	3 hour(s)
Replacement Battery	APCRBC117
RBC Quantity	0

Communications & Management

Interface Port(s)	SmartSlot
Available SmartSlot™ Interface Quantity	0
Control panel	LED status display with On Line : On Battery : Replace Battery and Overload indicators , Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency Power Off (EPO)	Yes

Surge Protection and Filtering

Surge energy rating	645 joules
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Physical

Maximum Height	85.0 mm
Maximum Width	432.0 mm
Maximum Depth	667.0 mm
Rack Height	2 U
Net Weight	37.24 kg
Shipping Weight	45.26 kg
Shipping Height	243.0 mm
Shipping Width	596.0 mm
Shipping Depth	869.0 mm
Master Carton Units	1.0
Master Carton Weight	0.0 lbs
Color	Black
Units per Pallet	8.0
# of Layers per Pallet	4
# of Units per Layer per Pallet	2
Pallet Weight	387.88 kg

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 %
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95 %
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	55.000 dB
Online Thermal Dissipation	184.000 BTU/hr

Conformance

Standard warranty	3 years repair or replace (excluding battery) and 2 years for battery
-------------------	---

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs
Battery Directive	Compliant
Battery Notes	Battery Notes