

# Product data sheet

Specifications



## APC Smart-UPS X 750VA Tower/ Rack 120V with bundled network management card (NMC) (Not for sale in CO, VT or WA)

SMX750-NMC

⚠ Discontinued

⚠ Discontinued on: Jun 10, 2022

### Overview

Lead time Usually Ships within 2 Weeks

### Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Rated power in W	600 W
Rated power in VA	750 VA
Input Connection Type	NEMA 5-15P
output connection type	8 NEMA 5-15R
Number of rack unit	2U
Cable length	2.4 m
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	CD with software Documentation CD Installation guide Rack mounting brackets Removable support feet Smart UPS signalling RS-232 cable USB cable Web/SNMP management card

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>
Extended runtime	1
Number of battery filled slots	1
Number of battery free slots	1
Battery recharge time	3 h
Number of battery replacement quantity	1
Overcurrent protection	60 A
Battery life	3...5 year(s)
Replacement battery	<a href="#">APCRBC116</a>

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Battery charger power	104 W rated
-----------------------	-------------

## General

Number of power module filled slots	0
Number of power module free slots	0
product web sub-family	Extended run
Redundant	No

## Physical

Colour	Black
Height	43.2 cm
Width	8.9 cm
Depth	49 cm
net weight	22.05 kg
Mounting preference	Lower
mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	Yes

## Input

Maximum input current	12 A
Max short time withstand current	1000 kA
Switching current capacity	15 A
Input voltage limits	75...154 V adjustable 82...143 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

## Output

Harmonic distortion	Less than 5 %
Maximum configurable power in VA	750 VA
Maximum configurable power in W	600 W
UPS type	Line interactive
Wave type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

## Conformance

Product certifications	cUL listed
Equipment protection policy	Lifetime : \$150000

## Environmental

Acoustic level	40 dBA
heat dissipation	69 Btu/h

Operating altitude	0...10000 ft
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.0000000000...15240.0000000000 m
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %

## Communications & Management

control panel	Multifunction LCD status and control console
Emergency power off	Yes
Free slots	0
Preinstalled device	Network management card
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

Surge energy rate	645 J
Noise suppression	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : meets UL 1449

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	58.9 cm
Package 1 Width	24.6 cm
Package 1 Length	62 cm
Package 1 Weight	26.444 kg

## Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---

## Sustainability

**Green Premium™** label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient   Take-back   Transparency   RoHS/REACH

## Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

## Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information   [Yes](#)

## Certifications & Standards

Reach Regulation   [REACH Declaration](#)

Eu Rohs Directive   Compliant with Exemptions

Environmental Disclosure   [Product Environmental Profile](#)

Circularity Profile   [End of Life Information](#)

California Proposition 65   WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)