



Overview

| | |
|-----------|------------------|
| Lead time | Usually in Stock |
|-----------|------------------|

General

| | |
|-------------------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Provided equipment | Basic UPS signalling RS-232 cable CD with software Country-specific detachable power cord User manual USB cable |
| Max runtime | 4 min |
| Number of tare power | 41 W |
| Number of power module free slots | 0 |
| Number of power module filled slots | 0 |
| Redundant | No |
| UPS size | WS |

Physical

| | |
|---------------------|--------------------|
| Cable length | 1.50 m |
| Colour | Black |
| Depth | 40 cm |
| Height | 23.8 cm |
| Mounting preference | No preference |
| Net weight | 16.8 kg |
| Mounting mode | Not rack-mountable |
| Two post mountable | 0 |
| USB compatible | Yes |
| Width | 14.5 cm |

Input

| | |
|----------------------|------------------------------------|
| Network frequency | 40...70 Hz |
| Plug standard | CH1-10P China |
| Input voltage limits | 110...300 V adjustable (half load) |

| | |
|----------------------------|----------------|
| Inputvolt_other | 230 V 240 V |
| Maximum input current | 9 A |
| Switching current capacity | 10 A |
| Number of cables | 1 |
| Input voltage | 220 V |
| Cos phi | 0.95 |

Output

| | |
|----------------------------------|----------------------------------------|
| Rated power in W | 1600 W |
| Maximum configurable power in W | 1600 W |
| Output frequency | 50/60 Hz +/- 3 Hz sync to mains |
| Outputvolt_other | 230 V 240 V |
| Crest factor | 3 : 1 |
| UPS type | Double conversion online |
| Wave type | Sine wave |
| Nb of power socket outlets | 4 chinese outlet |
| Bypass type | Internal bypass (automatic and manual) |
| Curve equation | Efficiency |
| Curve load maximum | 100 % |
| Curve X-axis maximum | 100 % |
| Curve X-axis minimum | 0 % |
| Curve X-axis title | Load |
| Curve X-axis units | Percentage |
| Curve Y-axis maximum | 100 % |
| Curve Y-axis minimum | 50 % |
| Curve Y-axis title | Efficiency |
| Curve Y-axis units | Percentage |
| Efficiency | 88 % (full load) |
| Graph display | 1 |
| Output voltage | 220 V |
| Maximum configurable power in VA | 2000 VA |
| Rated power in VA | 2000 VA |

Conformance

| | |
|------------------------|----|
| Product certifications | CE |
|------------------------|----|

Environmental

| | |
|---------------------------------------|-------------------------|
| Ambient air temperature for operation | 0...40 °C |
| Relative humidity | 0...95 % non-condensing |
| Operating altitude | 0...10000 ft |
| Ambient air temperature for storage | -20...50 °C |
| Storage altitude | 0.00...15240.00 m |
| Acoustic level | 50 dBA |
| Show note OP temperature | No |
| IP degree of protection | IP20 |

Batteries & Runtime

| | |
|--------------------------------|-------------------|
| Battery type | Lead-acid battery |
| Number of battery filled slots | 0 |
| Number of battery free slots | 0 |

| | |
|------------------------|----------------------------------------------------------|
| Battery recharge time | 4 h |
| Additional information | Configurable for 220 : 230 or 240 nominal output voltage |
| Liquid value | 0 |
| Battery voltage | 48 V |
| Battery curve | D |
| Battery charger power | 76 W rated |
| Battery power in VAH | 304 VAh runtime 0 VAh runtime |
| Extended runtime | 0 |

Communications & Management

| | |
|---------------|----------------------------------------------------------------------------------------|
| Control panel | Multifunction LCD status and control console |
| Alarm | Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm |

Surge Protection and Filtering

| | |
|-------------------|-------|
| Surge energy rate | 600 J |
|-------------------|-------|

Packing Units

| | |
|------------------|----------------|
| Package 1 Weight | 18.1 kg |
| Package 1 Height | 33 cm |
| Package 1 width | 23.5 cm |
| Package 1 Length | 47.7 cm |
| SCC14 | 10731304343186 |

Offer Sustainability

| | |
|-------------------|---------------------|
| EU RoHS Directive | Under investigation |
|-------------------|---------------------|

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|