



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	Basic UPS signalling RS-232 cable CD with software Country-specific detachable power cord 1 x DC cable User manual USB cable
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS

Physical

Cable length	1.50 m
Colour	Black
Depth	40 cm
Height	23.8 cm
Mounting preference	No preference
Net weight	7.4 kg
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes
Width	14.5 cm

Input

Network frequency	40...70 Hz
Plug standard	CH1-10P China
Input voltage limits	110...300 V adjustable (half load)
Inputvolt_other	230 V

	240 V
Switching current capacity	10 A
Number of cables	1
Input voltage	220 V

Output

Rated power in W	1600 W
Maximum configurable power in W	1600 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Outputvoltage_other	230 V 240 V
Crest factor	3 : 1
UPS type	Double conversion online
Wave type	Sine wave
Nb of power socket outlets	4 chinese outlet
Bypass type	Internal bypass (automatic and manual)
Curve equation	Efficiency
Curve load maximum	100 %
Curve X-axis maximum	100 %
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Efficiency	88 % (full load)
Graph display	1
Output voltage	220 V
Maximum configurable power in VA	2000 VA
Rated power in VA	2000 VA

Conformance

Product certifications	CE
------------------------	----

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-20...50 °C
Storage altitude	0.00...15240.00 m
Acoustic level	50 dB
Show note OP temperature	No
IP degree of protection	IP20

Batteries & Runtime

Battery type	External battery system
Number of battery filled slots	0
Number of battery free slots	0
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Liquid value	0
Battery voltage	72 V

Battery curve	B
Battery power in VAH	0 VAh runtime
Extended runtime	0

Communications & Management

Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

Packing Units

Package 1 Weight	9.1 kg
Package 1 Height	33 cm
Package 1 width	23.5 cm
Package 1 Length	47.7 cm
SCC14	10731304346590

Offer Sustainability

EU RoHS Directive	Under investigation
-------------------	---------------------

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------