# **Product data sheet**

Specifications





# Schneider Electric On-Line UPS 1000VA, 230V, 6x IEC 60320 C13 & 2x IEC Jumpers outlets

SR11KXIET

(!) Discontinued

#### **Overview**

Presentation	Proven Industrial UPS power protection for control applications and harsh environments.
Lead Time	Usually in Stock
Main	
Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Kw Rating	700 W
Rated Power In Va	1000 VA
Input Connection Type	IEC 60320 C14
Output Connection Type	6 IEC 60320 C13 2 IEC Jumpers
Number Of Rack Unit	2U
Number Of Cables	1
Provided Equipment	CD with software Smart UPS signalling RS-232 cable User Manual

#### **Batteries & Runtime**

Run Time	View Runtime Graph ☐
Efficiency	View Efficiency Graph ☐
Battery Type	Lead-Acid battery
Included Battery Modules	1
Battery Slots Empty	0
Typical Recharge Time	3 h
Rbc Quantity	1
Battery Charge Power (Watts)	109 W rated
Battery Life	35 year(s)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Replacement Battery	RBC31 ☐ RBC57 ☐
Extendable Run Time	1

## General

Topology	Double Conversion Online
Number Of Power Module	700
Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

# **Physical**

_	
Color	Black
Height	17.01 in (43.2 cm)
Width	3.35 in (8.5 cm)
Depth	19.02 in (48.3 cm)
Net Weight	50.71 lb(US) (23 kg)
Mounting Location	Front
Mounting Preference	Lower
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

# Input

Input Frequency	50/60 Hz +/- 5 Hz auto-sensing
Efficiency At Full Load	160280 V

# Output

Maximum Configurable Power In Va	1000 VA
Max Configurable Power (Watts)	700 W
Output Frequency (Sync To Mains)	50/60 Hz +/- 3 Hz user adjustable +/- 0.1 sync to mains
Wave Type	Sine wave
Harmonic Distortion	Less than 3%
Crest Factor	3:1
Bypass Type	Built-in Bypass
Additional Information	Configurable for 220 : 230 or 240 nominal output voltage

# Conformance

Product Certifications	C-tick	
	CE	
	GOST	
	VDE	

Standards EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

#### **Environmental**

Ambient Air Temperature For Operation	32104 °F (040 °C)
Relative Humidity	095 % non-condensing
Operating Altitude	010000 ft
Ambient Air Temperature For Storage	-4122 °F (-2050 °C)
Storage Relative Humidity	095 % non-condensing
Storage Altitude	050000 ft (0.0015240.00 m)
Acoustic Level	50 dBA
Heat Dissipation	324 Btu/h
Ip Degree Of Protection	IP20

## **Communications & Management**

Free Slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency Power Off (Epo)	Optional

## **Surge Protection and Filtering**

Surge Energy Rating	420 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m

# Ordering and shipping details

Gtin	731304315841
Country Of Origin	PH

# **Packing Units**

=	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	11.26 in (28.6 cm)
Package 1 Width	24.80 in (63 cm)
Package 1 Length	23.39 in (59.4 cm)
Package 1 Weight	61.29 lb(US) (27.8 kg)

## **Contractual warranty**

Warranty	2 years repair or replace, optional on-site warranties available, optional extended
	warrantias available

warranties available

# Sustainability Screen Premium\*

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

#### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information.
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Circularity Profile	End of Life Information