

# Product data sheet

Specifications



## Schneider Electric On-Line UPS 2000VA, 230V, 6x IEC 60320 C13 & 2x IEC Jumpers outlets

SR12KXIET

! Discontinued

### Overview

Presentation	Proven Industrial UPS power protection for control applications and harsh environments.
Lead Time	Usually in Stock

### Main


Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Kw Rating	1400 W
Rated Power In Va	2000 VA
Input Connection Type	BS1363A British IEC 60320 C20 Schuko CEE 7 / EU1-16P
Output Connection Type	6 IEC 60320 C13 2 IEC Jumpers
Number Of Rack Unit	2U
Cable Length	8 ft (2.44 m)
Number Of Cables	1
Provided Equipment	CD with software Smart UPS signalling RS-232 cable User Manual

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>
Battery Type	Lead-Acid battery
Included Battery Modules	1
Battery Slots Empty	0
Typical Recharge Time	4 h
Rbc Quantity	1
Battery Charge Power (Watts)	79 W rated

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Battery Life	3...5 year(s)
Replacement Battery	<a href="#">RBC31</a> 
Extendable Run Time	1

## General

Topology	Double Conversion Online
Number Of Power Module	1400
Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

## Physical

Color	Black
Height	17.01 in (43.2 cm)
Width	3.35 in (8.5 cm)
Depth	19.02 in (48.3 cm)
Net Weight	55.12 lb(US) (25 kg)
Mounting Location	Front
Mounting Preference	Lower
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

## Input

Input Frequency	50/60 Hz +/- 5 Hz auto-sensing
Efficiency At Full Load	160...280 V

## Output

Maximum Configurable Power In Va	2000 VA
Max Configurable Power (Watts)	1400 W
Output Frequency (Sync To Mains)	50/60 Hz +/- 3 Hz user adjustable +/- 0.1 sync to mains
Wave Type	Sine wave
Harmonic Distortion	Less than 3%
Crest Factor	3 : 1
Bypass Type	Built-in Bypass
Additional Information	Configurable for 220 : 230 or 240 nominal output voltage

## Conformance

Product Certifications	C-tick CE GOST VDE
------------------------	-----------------------------

Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
-----------	--

## Environmental

Ambient Air Temperature For Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	-4...122 °F (-20...50 °C)
Storage Relative Humidity	0...95 % non-condensing
Storage Altitude	0...50000 ft (0.00...15240.00 m)
Acoustic Level	50 dBA
Heat Dissipation	543 Btu/h
Ip Degree Of Protection	IP20

## Communications & Management

Free Slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency Power Off (Epo)	Optional

## Surge Protection and Filtering

Surge Energy Rating	420 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m

## Ordering and shipping details

Gtin	731304315865
------	--------------

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	11.26 in (28.6 cm)
Package 1 Width	24.80 in (63 cm)
Package 1 Length	23.39 in (59.4 cm)
Package 1 Weight	65.74 lb(US) (29.82 kg)
Unit Type Of Package 2	P12
Number Of Units In Package 2	6
Package 2 Height	46.06 in (117 cm)
Package 2 Width	31.50 in (80 cm)
Package 2 Length	47.24 in (120 cm)
Package 2 Weight	496.04 lb(US) (225 kg)

## Contractual warranty

Warranty	2 years repair or replace, optional on-site warranties available, optional extended warranties available
----------	--

# Sustainability



**Green Premium™ label** is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)

## Well-being performance

 Mercury Free	
 Rohs Exemption Information	<a href="#">Yes</a>
Reach Regulation	<a href="#">REACH Declaration</a>
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information.
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.