

Product data sheet

Specifications



APC Smart-UPS RC 3000VA,
230V, no battery, LCD, 2x IEC
60320 C13 outlets

SRC3KUXI

Overview

Lead Time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated Power In W	2400 W
Rated Power In Va	3000 VA
Nb Of Power Socket Outlets	2 IEC 60320 C13
Output Connector Type	Hard wire 3-wire (H N + E) 1
Battery Type	External battery system
Provided Equipment	Basic UPS signalling RS-232 cable Installation guide User manual

Batteries & Runtime

Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Additional Information	72V. SMF or Flooded battery compatible. Internal charger 2A - 13A programmable Configurable for 220 : 230 or 240 nominal output voltage
Battery Power In Vah	0 VAh runtime
Extended Runtime	0

General

Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

Physical

Height	43.2 cm
Width	8.5 cm
Depth	48.3 cm
Net Weight	11.5 kg

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

Input

Network Frequency	40...70 Hz
Number Of Input Connectors	1 hard wire 3-wire (1P + N + E)
Input Voltage Limits	140...280 V
Load Power Factor	0.8

Output

Maximum Configurable Power In W	2400 W
Harmonic Distortion	Less than 3 %
Output Frequency	50/60 Hz +/- 3 Hz sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised 60 Hz +/- 0.1 % for 60 Hz nominal unsynchronised
Crest Factor	3 : 1
Ups Type	Double conversion online
Wave Type	Sine wave
Output Harmonic Distortion	< 3% linear load
Bypass Type	Built-in bypass
Efficiency	93 % (full load) 92.3 % (half load)
Maximum Configurable Power In Va	3000 VA
Transfer Time	4 ms typical

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 %
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	0...45 °C
Storage Relative Humidity	0...95 %
Storage Altitude	0.00...4572.00 m
Acoustic Level	55 dBA

Communications & Management

Free Slots	1
Control Panel	Multifunction LCD status and control console
Alarm	Audible and visible alarms prioritized by severity
Emergency Power Off	Yes

Surge Protection and Filtering

Noise Suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449
-------------------	---

Packing Units

Package 1 Height	57.5 cm
Package 1 Width	26.5 cm
Package 1 Length	58.5 cm
Package 1 Weight	14.5 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. **Green Premium** promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low- products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant
[EU RoHS Declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)