

Product data sheet

Specifications



APC Smart-UPS RC 5000VA, 230V, no battery, rackmount w/kit, 2U

SRC5000UXICH

 **Discontinued on:** Jun 10, 2022

 **Discontinued**


Overview

Lead time Usually in Stock

Main

Main Input Voltage	230 V
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	3500 W
Rated power in VA	5000 VA
Output connector type	Hard wire 3-wire (H N + E) 1
Number of rack unit	2U
Provided equipment	CD with software Rack mounting brackets Smart UPS signalling RS-232 cable User manual

Batteries & Runtime

Run Time	View Runtime Graph 
Battery type	External battery system
Number of battery filled slots	0
Number of battery free slots	1
Battery life	3...5 year(s)
Extended runtime	1

General

UPS type	Double conversion online
Number of power module	1400
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Physical

Colour	Black
Height	44 cm
Width	8.9 cm
Depth	67.8 cm
net weight	15 kg
mounting location	Front
Mounting preference	Lower
mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	No

Input

Network frequency	40...70 Hz auto-sensing
Number of input connectors	1 hard wire 3-wire (1P + N + E)
Input voltage limits	160...280 V
Maximum input current	37 A
Switching current capacity	40 A
Input harmonic distortion	Less than 9 % for full load

Output

Maximum configurable power in VA	5000 VA
Maximum configurable power in W	3500 W
Output frequency	50/60 Hz +/- 3 Hz user adjustable +/- 0.1 Hz sync to mains
Wave type	Sine wave
Efficiency	90 % (full load)
Harmonic distortion	Less than 3 %
Crest factor	3 : 1
Bypass type	Built-in bypass
Additional information	Unit ships without batteries. Configurable for 220 : 230 or 240 nominal output voltage

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-20...50 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.000000000...15240.0000000000 m
Acoustic level	60 dBA
heat dissipation	652 Btu/h

Communications & Management

Free slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency power off	Optional

Surge Protection and Filtering

Surge energy rate	420 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	22 cm
Package 1 Width	60 cm
Package 1 Length	80 cm
Package 1 Weight	19.958 kg

Contractual warranty

Warranty	2 years repair or replace, optional on-site warranties available, optional extended warranties available
----------	--

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)