

# Product data sheet

Specifications



APC Smart-UPS On-Line,  
2200VA, Tower, 230V, 8x C13+2x  
C19 IEC outlets, SmartSlot,  
Extended runtime, W/O rail kit

SRT2200XLI

## Overview

|              |                                                                                 |
|--------------|---------------------------------------------------------------------------------|
| Presentation | High density, double-conversion on-line power protection with scalable runtime. |
| Lead Time    | Usually in Stock                                                                |

## Main

|                            |                                                                                                                                                              |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Main Input Voltage         | 230 V                                                                                                                                                        |
| Other Input Voltage        | 220 V<br>240 V                                                                                                                                               |
| Main Output Voltage        | 230 V                                                                                                                                                        |
| Other Output Voltage       | 220 V<br>240 V                                                                                                                                               |
| Rated Power In W           | 1980 W                                                                                                                                                       |
| Rated Power In Va          | 2200 VA                                                                                                                                                      |
| Input Connection Type      | BS1363A British<br>IEC 60320 C20<br>Schuko CEE 7 / EU1-16P                                                                                                   |
| Nb Of Power Socket Outlets | 8 IEC 60320 C13<br>2 IEC Jumpers<br>2 IEC 60320 C19                                                                                                          |
| Cable Length               | 2.44 m                                                                                                                                                       |
| Number Of Cables           | 1                                                                                                                                                            |
| Battery Type               | Lead-acid battery                                                                                                                                            |
| Provided Equipment         | CD with software<br>Country-specific detachable power cord<br>Documentation CD<br>Installation guide<br>Removable support feet<br>USB cable<br>Warranty card |

## Batteries & Runtime

|                                        |                                                          |
|----------------------------------------|----------------------------------------------------------|
| Run Time                               | <a href="#">View Runtime Graph</a>                       |
| Efficiency                             | <a href="#">View Efficiency Graph</a>                    |
| Number Of Battery Filled Slots         | 1                                                        |
| Number Of Battery Free Slots           | 0                                                        |
| Battery Recharge Time                  | 3 h                                                      |
| Number Of Battery Replacement Quantity | 1                                                        |
| Additional Information                 | Configurable for 220 : 230 or 240 nominal output voltage |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

|                       |                                                                                                                                                                                                                              |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Battery Voltage       | 72 V                                                                                                                                                                                                                         |
| Battery Charger Power | 122 W rated                                                                                                                                                                                                                  |
| Battery Power In Vah  | 367 VAh runtime                                                                                                                                                                                                              |
| Battery Life          | 3...5 year(s)                                                                                                                                                                                                                |
| Replacement Battery   | <a href="#">APCRBC141</a> <br><a href="#">SRT72RMBPUS</a>  |
| Battery Option        | SRT72BP 1 1101 VAh<br>SRT72BP 2 1835 VAh<br>SRT72BP 3 2569 VAh<br>SRT72BP 4 3303 VAh<br>SRT72BP 5 4037 VAh<br>SRT72BP 6 4771 VAh<br>SRT72BP 8 6239 VAh<br>SRT72BP 10 7707 VAh                                                |
| Extended Runtime      | 1                                                                                                                                                                                                                            |

## General

|                                     |              |
|-------------------------------------|--------------|
| Product Web Sub-Family              | High density |
| Number Of Power Module              | 1400         |
| Number Of Power Module Free Slots   | 0            |
| Number Of Power Module Filled Slots | 0            |
| Redundant                           | No           |

## Physical

|                     |                       |
|---------------------|-----------------------|
| Colour              | Black                 |
| Height              | 43.2 cm               |
| Width               | 8.5 cm                |
| Depth               | 58.4 cm               |
| Net Weight          | 25 kg                 |
| Mounting Location   | Front                 |
| Mounting Preference | Lower                 |
| Mounting Mode       | Rack-mounted with kit |
| Two Post Mountable  | 0                     |
| Usb Compatible      | Yes                   |
| Mounting Position   | Vertical              |

## Input

|                      |                                    |
|----------------------|------------------------------------|
| Network Frequency    | 40...70 Hz auto-sensing            |
| Input Voltage Limits | 100...275 V adjustable (half load) |

## Output

|                                 |                                 |
|---------------------------------|---------------------------------|
| Maximum Configurable Power In W | 1980 W                          |
| Harmonic Distortion             | Less than 2 %                   |
| Output Frequency                | 50/60 Hz +/- 3 Hz sync to mains |
| Crest Factor                    | 3 : 1                           |

|                                  |                                        |
|----------------------------------|----------------------------------------|
| Ups Type                         | Double conversion online               |
| Wave Type                        | Sine wave                              |
| Bypass Type                      | Internal bypass (automatic and manual) |
| Maximum Configurable Power In Va | 2200 VA                                |

## Conformance

|                        |                                  |
|------------------------|----------------------------------|
| Product Certifications | CE<br>EAC<br>RCM<br>VDE          |
| Marking                | CE Mark                          |
| Standards              | EN/IEC 62040-1<br>EN/IEC 62040-2 |

## Environmental

|                                       |                         |
|---------------------------------------|-------------------------|
| Ambient Air Temperature For Operation | 0...40 °C               |
| Relative Humidity                     | 0...95 % non-condensing |
| Operating Altitude                    | 0...10000 ft            |
| Ambient Air Temperature For Storage   | -15...45 °C             |
| Storage Relative Humidity             | 0...95 % Non-condensing |
| Storage Altitude                      | 0.00...15240.00 m       |
| Acoustic Level                        | 55 dBA                  |
| Heat Dissipation                      | 703 Btu/h               |
| Ip Degree Of Protection               | IP20                    |

## Communications & Management

|                     |                                                    |
|---------------------|----------------------------------------------------|
| Free Slots          | 1                                                  |
| Control Panel       | Multifunction LCD status and control console       |
| Alarm               | Audible and visible alarms prioritized by severity |
| Emergency Power Off | Yes                                                |

## Surge Protection and Filtering

|                   |       |
|-------------------|-------|
| Surge Energy Rate | 340 J |
|-------------------|-------|

## Packing Units

|                              |          |
|------------------------------|----------|
| Package 1 Weight             | 30.84 kg |
| Package 1 Height             | 24.6 cm  |
| Package 1 Width              | 59.9 cm  |
| Package 1 Length             | 81 cm    |
| Number Of Units In Package 3 | 12       |

## Contractual warranty

|          |                                                                       |
|----------|-----------------------------------------------------------------------|
| Warranty | 3 years repair or replace (excluding battery) and 2 years for battery |
|----------|-----------------------------------------------------------------------|

## Sustainability

**Green Premium™** label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. **Green Premium** promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low- products. **Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)



Energy Efficient   Take-back   Transparency   RoHS/REACH

## Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

## Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information   [Yes](#)

## Certifications & Standards

|                          |                                                                                                                             |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Reach Regulation         | <a href="#">REACH Declaration</a>                                                                                           |
| Eu Rohs Directive        | Compliant<br><a href="#">EU RoHS Declaration</a>                                                                            |
| Environmental Disclosure | <a href="#">Product Environmental Profile</a>                                                                               |
| Weee                     | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |
| Circularity Profile      | <a href="#">End of Life Information</a>                                                                                     |