



### Overview

Lead time	Usually in Stock
-----------	------------------

### General

Provided equipment	Basic UPS signalling RS-232 cable CD with software User manual USB cable
Max runtime	4 min
Number of tare power	41 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS

### Physical

Cable length	1.50 m
Colour	Black
Depth	28.8 cm
Height	22.3 cm
Net weight	9.3 kg
USB compatible	Yes
Width	14.5 cm

### Input

Network frequency	40...70 Hz
Plug standard	IEC 60320 C14
Input voltage limits	110...285 V adjustable (half load) 160...280 V
Inputvolt_other	220 V 240 V
Number of cables	1

Input voltage	230 V
---------------	-------

## Output

Rated power in W	1600 W
Maximum configurable power in W	1600 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Outputvolt_other	220 V 240 V
Crest factor	3 : 1
UPS type	Double conversion online
Wave type	Sine wave
Nb of power socket outlets	3 Argentinean
Bypass type	Internal bypass (automatic and manual)
Curve equation	Efficiency
Curve fixed loss	0.0285
Curve load maximum	100 %
Curve load minimum	4 %
Curve proportional loss	0.0517
Curve square loss	0.0279
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit of data measured in accordance with the ENERGY STAR Test Method for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 230V/50Hz electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Efficiency	88 % (full load)
Graph display	1
Output voltage	230 V 240 V
Maximum configurable power in VA	2000 VA
Rated power in VA	2000 VA

## Conformance

Product certifications	CE IRAM
------------------------	------------

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-20...50 °C
Storage altitude	0.00...15240.00 m
Acoustic level	50 dBA
Show note OP temperature	No
IP degree of protection	IP20

## Batteries & Runtime

Battery type	Lead-acid battery
--------------	-------------------

Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	4 h
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Liquid value	0
Battery curve	D
Battery charger power	76 W rated
Battery power in VAH	305 VAh runtime

### Communications & Management

Free slots	1
Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

### Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

### Packing Units

Package 1 Weight	10.6 kg
Package 1 Height	33 cm
Package 1 width	23.5 cm
Package 1 Length	36.5 cm
SCC14	10731304340215

### Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------