



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	CD with software User manual USB cable
Number of tare power	40 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS

Physical

Depth	42.5 cm
Height	33.6 cm
Net weight	45.9 kg
USB compatible	No
Width	19 cm

Input

Network frequency	40...70 Hz
Inputvolt_other	220 V 240 V
Input voltage	230 V

Output

Rated power in W	2400 W
Maximum configurable power in W	2400 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Outputvolt_other	220 V

	240 V
Crest factor	3 : 1
Wave type	Sine wave
Nb of power socket outlets	4 Brazilian 2P+T
Bypass type	Internal bypass (automatic and manual)
Curve equation	Efficiency
Curve fixed loss	0.0229
Curve load maximum	100 %
Curve load minimum	3 %
Curve proportional loss	0.0382
Curve square loss	0.0289
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit of data measured in accordance with the ENERGY STAR Test Method for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 230V/50Hz electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Efficiency	88 % (full load)
Graph display	1
Output voltage	230 V
Maximum configurable power in VA	3000 VA
Rated power in VA	3000 VA

Environmental

Show note OP temperature	No
--------------------------	----

Batteries & Runtime

Number of battery filled slots	0
Number of battery free slots	0
Additional information	Configurable for 220 : 230 or 240 nominal output voltage
Liquid value	0
Battery curve	D
Battery charger power	93900 W rated
Battery power in VAh	939 VAh runtime
Battery option	SRV72BP-9A 1 1878 VAh SRV72BP-9A 2 2817 VAh SRV72BP-9A 3 3756 VAh SRV72BP-9A 4 4695 VAh

Packing Units

Package 1 Weight	49.8 kg
Package 1 Height	46.5 cm
Package 1 width	32.5 cm
Package 1 Length	56.5 cm

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------