



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	CD with software User manual USB cable
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS

Physical

Depth	44.7 cm
Height	33.6 cm
Net weight	16.5 kg
USB compatible	No
Width	19 cm

Input

Network frequency	40...70 Hz
Number of input connectors	1 hard wire 3-wire
Inputvolt_other	220 V 240 V
Input voltage	230 V

Output

Rated power in W	10000 W
Maximum configurable power in W	10000 W
Outputvolt_other	220 V 240 V

Crest factor	3 : 1
UPS type	Double conversion online
Wave type	Sine wave
Curve equation	Efficiency
Curve load maximum	100 %
Curve X-axis maximum	100 %
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	2
Half load runtime	00:07:00 5000 W
Output voltage	230 V
Maximum configurable power in VA	10000 VA
Rated power in VA	10000 VA

Conformance

Product certifications	CE EAC
Standards	IEC 62040-1-1 IEC 62040-1-2

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...3000 m
Storage altitude	0...15000 m
Show note OP temperature	No

Batteries & Runtime

Battery type	External battery system
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Liquid value	0
Battery curve	B

Communications & Management

Control panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency power off	Yes

Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

Packing Units

Package 1 Weight	19.5 kg
Package 1 Height	46 cm

Package 1 width	29 cm
Package 1 Length	57 cm

Offer Sustainability

REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------