



Trailing lead, Unica extend, 5 Schuko, USB type A+A, 1.5m cable, anthracite

ST945U1B

VI	а	ı	r	1

Range	Unica
Product or component type	Trailing lead
Aesthetic name	Unica extend
Control type	Mains switch
Socket number	5
Integrated connection type	2 USB type A 5 V DC, maximum load current: 2.4 A
Colour tint	Anthracite (RAL 7021)
Cable length	1.5 m

Complementary

Type of USB power supply	USB type A + A
Number of USB connection	2
[Ue] rated operational voltage	250 V
On/Off switch present	True
[In] rated current	16 A
Outlet poles configuration	2P + E
Outlet standard	Schuko
Socket additional information	Shuttered
Maximum switching capacity	16 A
Pilot light	ON indicator
Material	PP (polypropylene)
Length	339 mm
Width	57 mm
Depth	40.5 mm
Type of packing	Blister
Surface treatment	Untreated

Packing Units

Unit Type of Package 1 PCE

Number of Units in Package 1	1
Package 1 Height	4.5 cm
Package 1 Width	13.6 cm
Package 1 Length	41.5 cm
Package 1 Weight	467.0 g
Unit Type of Package 2	S04
Number of Units in Package 2	24
Package 2 Height	30.0 cm
Package 2 Width	40.0 cm
Package 2 Length	60.0 cm
Package 2 Weight	14.887 kg
Unit Type of Package 3	P06
Number of Units in Package 3	96
Package 3 Height	77.0 cm
Package 3 Width	80.0 cm
Package 3 Length	60.0 cm
Package 3 Weight	68.048 kg

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
Mercury free	Yes	
Sustainable packaging	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
RoHS exemption information	Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	End of Life Information	

Recommended replacement(s)