

Product data sheet

Specifications



APC Smart-UPS 1000VA RM 2U 120V



SU1000RM2U

Discontinued on: Jun 10, 2022

Discontinued

Overview

Lead Time Usually in Stock

Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Rated Power In W	670 W
Rated Power In Va	1000 VA
Input Connection Type	NEMA 5-15P
Nb Of Power Socket Outlets	6 NEMA 5-15R
Number Of Rack Unit	2U
Cable Length	2.44 m
Number Of Cables	1
Battery Type	Lead-acid battery
Provided Equipment	CD with software Rack mounting support rails Smart UPS signalling RS-232 cable User manual

Batteries & Runtime

Run Time	View Runtime Graph
Extended Runtime	0
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	3 h
Number Of Battery Replacement Quantity	1
Battery Life	4...6 year(s)
Replacement Battery	RBC23
Battery Power In Vah	336 VAh runtime
Battery Charger Power	112 W rated

General

Number Of Power Module Filled Slots 0

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number Of Power Module Free Slots	0
Redundant	No

Physical

Colour	Beige
Height	8.9 cm
Width	48.3 cm
Depth	45.7 cm
Net Weight	28.18 kg
Mounting Location	Front
Mounting Preference	No preference
Mounting Mode	Rack-mounted
Two Post Mountable	0
Usb Compatible	No

Input

Input Voltage Limits	75...154 V adjustable 82...144 V
Network Frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Crest Factor	Up to 5 : 1
Harmonic Distortion	Less than 5 % at full load
Maximum Configurable Power In Va	1000 VA
Maximum Configurable Power In W	670 W
Transfer Time	2 ms typical
Ups Type	Line interactive
Wave Type	Sine wave
Output Frequency	47...53 Hz for 50 Hz nominal sync to mains 57...63 Hz for 60 Hz nominal sync to mains

Conformance

Product Certifications	CSA
Equipment Protection Policy	Lifetime : \$150000
Standards	FCC part 15 class A UL 1778

Environmental

Acoustic Level	45 dBA
Heat Dissipation	89 Btu/h
Operating Altitude	0...10000 ft
Ambient Air Temperature For Operation	0...40 °C
Ambient Air Temperature For Storage	-15...45 °C

Storage Altitude	0.00...15240.00 m
Relative Humidity	0...95 %
Storage Relative Humidity	0...95 %

Communications & Management

Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Control Panel	LED status display with load and battery bar-graphs and on line : on battery : replace battery : and overload indicators
Emergency Power Off	Optional
Free Slots	1

Surge Protection and Filtering

Surge Energy Rate	459 J
Noise Suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Package 1 Weight	31.45 kg
Package 1 Height	25.1 cm
Package 1 Width	59.4 cm
Package 1 Length	60.3 cm

Contractual warranty

Warranty	2 years repair or replace, optional on-site warranties available, optional extended warranties available
----------	--