

Smart-UPS



APC Smart-UPS, 480 Watts / 750 VA,
Input 100V / Output 100V , Interface Port DB-9
RS-232, SmartSlot , Rack Height 1 U

Includes: Rack Mounting brackets, User Manual

Be the first to [write a review](#)

SU750RMJ1U
FINUED : recommended
 t product [SUA750RMJ1UB](#)

 [Email Technical Specifications](#)

 [Printer Friendly](#)

- Product Category**
- Computer and Peripheral (5)
 - Home UPS (2)
 - Network and Server
 - > **Smart-UPS**
 - > Smart-UPS On-Line
 - > Symmetra
 - Data Center and Facility 3 Phase (14)
 - UPS Management (7)

< Return to Uninterruptible Power Supply (UPS)

Technical Specifications

Product Overview

Documentation

Software & Firmware

Options

Ratings and Reviews

Output

Output Power Capacity	480 Watts / 750 VA
Max Configurable Power	480 Watts / 750 VA
Nominal Output Voltage	100V
Output Connections	(4) NEMA 5-15R 

Input

Nominal Input Voltage	100V	
Input Frequency	50/60 Hz +/- 5 Hz (auto sensing)	
Input Connections	NEMA 5-15P	
Cord Length	1.83 meters	
Input voltage range for main operations	75 - 119V	
Input voltage adjustable range for mains operation	70 - 125V	

Batteries & Runtime

Battery Type	Maintenance-free sealed Lead-Acid battery with suspended electrolyte : leakproof
Typical recharge time	4 hour(s)
RBC™ Quantity	4

Communications & Management

Interface Port(s)	DB-9 RS-232,SmartSlot
Available SmartSlot™ Interface Quantity	1
Control panel	LED status display with load and battery bar-graphs and On Line : On Battery : Replace Battery : and Overload Indicators
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency Power Off (EPO)	Optional

Physical

Maximum Height	44.00 mm
Maximum Width	483.00 mm
Maximum Depth	660.00 mm
Rack Height	1U
Net Weight	26.82 KG
Shipping Height	191.00 mm
Shipping Width	559.00 mm
Shipping Depth	775.00 mm
Color	Beige

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-3000 meters
Storage Temperature	-15 - 45 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters

Conformance

Regulatory Approvals	UL 1778,VCCI
Standard Warranty	2 years repair or replace,optional on-site warranties available,optional extended warranties available

^{**}The time to recharge to 90% of full battery capacity following a discharge to shutdown using a load rated for 1/2 the full load rating of the UPS