



### Commercial status

End of Commercialisation : JUN 10, 2022

⚠ End of Commercialisation

### Overview

Lead time	Usually in Stock
-----------	------------------

### Main

Main Input Voltage	120 V
Output voltage	120 V
Rated power in W	670 W
Rated power in VA	1000 VA
Input Connection Type	NBR 14136
Output connection type	6 NBR 14136
Number of rack unit	0U
Cable length	1.83 M
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	CD with software Smart UPS signalling RS-232 cable User manual USB cable

### Batteries & Runtime

Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 H
Number of battery replacement quantity	1
Battery life	3...5 Year(S)
Battery power in VAH	264 VAh runtime
Battery charger power	88 W rated

### General

Number of power module filled slots	0
Number of power module free slots	0
Redundant	No

## Physical

Colour	Black
Height	21.6 Cm
Width	17 Cm
Depth	43.9 Cm
Net weight	19.09 Kg
Mounting location	Front
Mounting preference	No preference
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes

## Input

Input voltage limits	75...154 V adjustable 82...144 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

## Output

Harmonic distortion	Less than 5 % at full load
Maximum configurable power in VA	1000 VA
Maximum configurable power in W	670 W
UPS type	Line interactive
Wave type	Sine wave
Output frequency	47...53 Hz for 50 Hz nominal sync to mains 57...63 Hz for 60 Hz nominal sync to mains

## Environmental

Acoustic level	41 dBA
Heat dissipation	100 Btu/H
Operating altitude	0...10000 ft
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.00...15240.00 M
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %

## Communications & Management

Control panel	LED status display with load and battery bar-graphs and on line : on battery : replace battery : and overload indicators
Emergency power off	Optional
Free slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays




## Surge Protection and Filtering

Surge energy rate	459 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	37 Cm
Package 1 Width	33 Cm
Package 1 Length	58 Cm
Package 1 Weight	21.954 Kg

### Offer Sustainability

REACH Regulation	<a href="#"> REACH Declaration</a>
EU RoHS Directive	Under investigation
Environmental Disclosure	<a href="#"> Product Environmental Profile</a>
Circularity Profile	<a href="#"> End Of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

### Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Product Life Status :	End of commercialisation
-----------------------	--------------------------