



Product data sheet

Specifications



APC Smart-UPS 1500VA 230V UL Approved

SUA1500IX38

-  To be discontinued on: Jun 30, 2024
-  To be end-of-service on: Jun 30, 2026

 Discontinued - Service only




Overview

Presentation	Intelligent and efficient power protection enabling multi-regional deployment.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Rated power in W	980 W
Rated power in VA	1500 VA
Input Connection Type	IEC 320 C14
output connection type	8 IEC 320 C13 2 IEC Jumpers
Cable length	2 m
Battery type	Lead-acid battery
Provided equipment	CD with software Smart UPS signalling RS-232 cable User manual USB cable

Batteries & Runtime

Run Time	View Runtime Graph 
Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Battery life	3...5 year(s)
Replacement battery	RBC7  SMT1500I-CH 
Battery charger power	136 W rated

General

Number of power module filled slots	0
-------------------------------------	---

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of power module free slots	0
Redundant	No

Physical

Height	21.6 cm
Width	17 cm
Depth	43.9 cm
net weight	24.09 kg
Mounting preference	No preference
mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Input

Input voltage limits	151...302 V adjustable 160...286 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Bypass type	Optional external bypass
Maximum configurable power in VA	1500 VA
Maximum configurable power in W	980 W
Transfer time	2 ms typical : 4 ms maximum
UPS type	Line interactive
Wave type	Sine wave
Output frequency	47...53 Hz for 50 Hz nominal sync to mains 57...63 Hz for 60 Hz nominal sync to mains

Conformance

Product certifications	C-Tick CE CSA GOST UL listed VDE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Acoustic level	45 dBA
heat dissipation	135 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.0000000000...15240.0000000000 m

Relative humidity	0...95 %
Storage Relative Humidity	0...95 %

Communications & Management

control panel	LED status display with load and battery bar-graphs and on line : on battery : replace battery : and overload indicators
Emergency power off	Optional
Free slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge energy rate	480 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	37 cm
Package 1 Width	59 cm
Package 1 Length	33 cm
Package 1 Weight	27 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Weee The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Circularity Profile [End of Life Information](#)

California Proposition 65 WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov