

APC Smart UPS 1500 VA 120V USB with alarm disabled

SUA1500X413

! Discontinued on: Jun 10, 2022

(!) Discontinued

Overview

Lead time	Usually Ships within 4 Weeks
Main	
Main Input Voltage	120 V
Main Output Voltage	120 V
Rated power in W	980 W
Rated power in VA	1440 VA
Input Connection Type	NEMA 5-15P
output connection type	8 NEMA 5-15R
Cable length	1.8 m
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	CD with software User manual USB cable

Batteries & Runtime

Battery charger power	136 W rated
	SMT1500I-CH ☐
Replacement battery	RBC7 ☐
Battery life	35 year(s)
Number of battery replacement quantity	1
Battery recharge time	3 h
Number of battery free slots	0
Number of battery filled slots	0
Extended runtime	0

General

Number of power module filled slots	0
Number of power module free slots	0
Redundant	No

Variant option Factory set voltage

Physical

•	
Colour	Black
Height	21.6 cm
Width	17 cm
Depth	43.9 cm
net weight	24.09 kg
mounting location	Front
Mounting preference	No preference
mounting mode	Not rack-mountable
USB compatible	Yes

Input

Input voltage limits	75154 V adjustable 82144 V
Network frequency	50/60 Hz +/- 3 Hz auto-sensing

Output

Harmonic distortion	Less than 5 % at full load
Maximum configurable power in VA	1440 VA
Maximum configurable power in W	980 W
UPS type	Line interactive
Wave type	Sine wave
Output frequency	4753 Hz for 50 Hz nominal sync to mains 5763 Hz for 60 Hz nominal sync to mains

Conformance

Equipment protection policy Lifetime: \$150000

Environmental

Acoustic level	45 dBA
heat dissipation	135 Btu/h
Operating altitude	010000 ft
Ambient air temperature for operation	040 °C
Ambient air temperature for storage	-1545 °C
Storage altitude	0.000000000015240.0000000000 m
Relative humidity	095 %
Storage Relative Humidity	095 %

Communications & Management

Emergency power off	Optional
Free slots	1

Alarm when on battery : distinctive low battery alarm : overload continuous tone

Surge Protection and Filtering

Surge energy rate	459 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	38.1 cm
Package 1 Width	33 cm
Package 1 Length	58.4 cm
Package 1 Weight	26.305 kg

Contractual warranty

Warranty 2 years repair or replace

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >







Energy Efficient Take-back Transparency

Resource performance

Energy Efficient Product

Take-Back Program Available

Well-being performance

Toxic Heavy Metal Free

Mercury Free

Reach Regulation

Eu Rohs Directive

Under investigation

Environmental Disclosure

Product Environmental Profile

Circularity Profile

End of Life Information