

# Product data sheet

Specifications



## APC Smart-UPS 1500VA USB & Serial 120V with AP9619 installed

SUA1500X448

 **Discontinued on:** Jun 10, 2022

 **Discontinued**




### Overview

Lead time Usually Ships within 2 Weeks

### Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Other Output Voltage	110 V
Rated power in W	980 W
Rated power in VA	1440 VA
Input Connection Type	NEMA 5-15P
output connection type	8 NEMA 5-15R
Cable length	1.8 m
Number of cables	1
Battery type	Lead-acid battery
Provided equipment	CD with software User manual USB cable Web/SNMP management card

### Batteries & Runtime

Run Time	<a href="#">View Runtime Graph</a> 
Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Battery life	3...5 year(s)
Replacement battery	<a href="#">RBC7</a>  <a href="#">SMT1500I-CH</a> 
Battery charger power	136 W rated

### General

Number of power module filled slots 0

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of power module free slots	0
Redundant	No
Variant option	Installed accessory

## Physical

Colour	Black
Height	21.6 cm
Width	17 cm
Depth	43.9 cm
net weight	24.09 kg
mounting location	Front
Mounting preference	No preference
mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

## Input

Input voltage limits	75...154 V adjustable 82...144 V
Network frequency	60 Hz +/- 3 Hz

## Output

Harmonic distortion	Less than 5 % at full load
Maximum configurable power in VA	1440 VA
Maximum configurable power in W	980 W
UPS type	Line interactive
Wave type	Sine wave
Output frequency	57...63 Hz for 60 Hz nominal sync to mains

## Conformance

Product certifications	CSA
Equipment protection policy	Lifetime : \$150000

## Environmental

Acoustic level	45 dBA
heat dissipation	135 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.0000000000...15240.0000000000 m
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %

## Communications & Management

control panel	LED status display with load and battery bar-graphs and on line : on battery : replace battery : and overload indicators
Emergency power off	Optional
Free slots	0
Preinstalled device	Network management card with environmental monitoring
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

Surge energy rate	459 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	38.1 cm
Package 1 Width	33 cm
Package 1 Length	58.4 cm
Package 1 Weight	26.305 kg

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient   Take-back   Transparency   RoHS/REACH

## Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

## Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information   [Yes](#)

## Certifications & Standards

Reach Regulation   [REACH Declaration](#)

Eu Rohs Directive   Compliant with Exemptions

Environmental Disclosure   [Product Environmental Profile](#)

Circularity Profile   [End of Life Information](#)