

# Product data sheet

Specifications



## APC Smart-UPS 3000VA USB & Serial Brazil 120V

SUA3000-BR

⚠ Discontinued on: Dec 31, 2017

⚠ End-of-service on: Jul 19, 2023

⚠ Discontinued

### Overview

Lead Time Usually in Stock

### Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Rated Power In W	2700 W
Rated Power In Va	3000 VA
Input Connection Type	NEMA L5-30P
Output Connection Type	6 NBR 14136
Cable Length	1.83 m
Number Of Cables	1
Battery Type	Lead-acid battery
Provided Equipment	CD with software Smart UPS signalling RS-232 cable User manual USB cable

### Batteries & Runtime

Efficiency	<a href="#">View Efficiency Graph</a>
Extended Runtime	0
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Replacement Battery	<a href="#">RBC55</a>

### General

Number Of Power Module Filled Slots	0
Number Of Power Module Free Slots	0
Redundant	No

### Physical

Height	43.2 cm
Width	19.6 cm

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Depth	54.6 cm
Net Weight	52.73 kg
Mounting Location	Front
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

## Input

Network Frequency	50/60 Hz +/- 3 Hz auto-sensing
-------------------	--------------------------------

## Output

Maximum Configurable Power In Va	3000 VA
Maximum Configurable Power In W	2700 W
Ups Type	Line interactive

## Environmental

Acoustic Level	45 dBA
Heat Dissipation	275 Btu/h
Operating Altitude	0...10000 ft
Ambient Air Temperature For Operation	0...40 °C
Ambient Air Temperature For Storage	-15...45 °C
Storage Altitude	0.00...15240.00 m
Relative Humidity	0...95 %
Storage Relative Humidity	0...95 %

## Communications & Management

Control Panel	LED status display with load and battery bar-graphs and on line : on battery : replace battery : and overload indicators
Free Slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

Surge Energy Rate	530 J
Noise Suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

## Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

## Sustainability

**Green Premium™ label** is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient   Take-back   Transparency   RoHS/REACH

## Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

## Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information   [Yes](#)

## Certifications & Standards

Reach Regulation   [REACH Declaration](#)

Eu Rohs Directive   Compliant with Exemptions

Environmental Disclosure   [Product Environmental Profile](#)

Circularity Profile   [End of Life Information](#)