



### Commercial status

This Product is Obsolete : MAR 29, 2023

 This Product is Obsolete

### Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable run-time. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead time	Usually in Stock

### Main

Main Input Voltage	120 V
Output voltage	120 V
Kw Rating	2850 W
Rated power in VA	3000 VA
Input Connection Type	NEMA L5-30P
Output connection type	6 NEMA 5-15R 2 NEMA 5-20R
Number of rack unit	2U
Cable length	10 Ft (3.05 m)
Number of cables	1
Battery Type	VRLA
Provided equipment	CD with software Installation guide Rack Mounting brackets Rack Mounting support rails Smart UPS signalling RS-232 cable User Manual USB cable Web/SNMP Management Card

## Batteries & Runtime

Extendable Run Time	1
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	3 H
RBC Quantity	1
Battery Life	3...5 Year(S)
Battery Charge Power (Watts)	199 W rated

## General

Number of power module filled slots	0
Number of power module free slots	0
Additional specification	Network card pre-installed
Redundant	No

## Physical

Color	Black
Height	3.39 In (8.6 cm)
Width	17.01 In (43.2 cm)
Depth	26.69 In (67.8 cm)
Net Weight	103.22 Lb(US) (46.82 kg)
Mounting Location	Front
Mounting preference	Lower
Mounting Mode	Rack-mounted
Two post mountable	0
USB compatible	No

## Input

Efficiency at full load	75...154 V adjustable 82...147 V
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing

## Output

Bypass type	Internal Bypass (Automatic and Manual)
Maximum configurable power in VA	3000 VA
Max Configurable Power (Watts)	2850 W
Maximum output current	24 A
Topology	Line Interactive
Efficiency at full load	95 % full load)

## Conformance

Product Certifications	BSMI[RETURN]CSA[RETURN]NOM[RETURN]VCCI
Equipment protection policy	Lifetime : \$150000

## Environmental

Acoustic level	55 dBA
Heat dissipation	300 Btu/H
Operating altitude	0...10000 ft
Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Ambient Air Temperature for Storage	23...131 °F (-5...55 °C)

Storage altitude	0...30000 Ft (0.00...9144.00 m)
Relative Humidity	0...95 %
Storage Relative Humidity	0...95 %

## Communications & Management

Control panel	LED status display with load and battery bar-graphs and On Line : On Battery : Replace Battery : Overload and Bypass Indicators
Emergency Power Off (EPO)	Optional
Free slots	0
Pre-Installed SmartSlot&trade; Cards	Network management card 2 with environmental monitoring
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

## Surge Protection and Filtering

Surge energy rating	540 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m

## Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	731304224563
Returnability	No

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.84 In (25 cm)
Package 1 Width	38.58 In (98 cm)
Package 1 Length	23.46 In (59.6 cm)
Package 1 Weight	125.27 Lb(US) (56.82 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Product Life Status : **End of commerc. - Block**

SUM3000RMXL2U may be replaced by any of the following products:

---



**SMX3000RMLV2U**

APC Smart-UPS X, Line Interactive, 3kVA, Rack/tower convertible 2U, 100V-127V, 3x 5-15R+3x 5-20R+1x L5-30R NEMA, Qty 1

Substitution date: |

---