

Product data sheet

Specifications



APC Smart-UPS RT 10kVA, 208V, 2x NEMA L6-20R & 2x NEMA L6-30R outlets

SURT10000XLT

Overview

Lead Time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	208 V
Other Input Voltage	240 V
Main Output Voltage	208 V
Other Output Voltage	240 V
Rated Power In W	8000 W
Rated Power In Va	10000 VA
Nb Of Power Socket Outlets	2 NEMA L6-20R 2 NEMA L6-30R
Output Connector Type	Hard wire 3-wire (2P + E) 1
Number Of Rack Unit	6U
Battery Type	Lead-acid battery
Provided Equipment	CD with software Service manual Smart UPS signalling RS-232 cable User manual Web/SNMP management card

Batteries & Runtime

Run Time	View Runtime Graph
Number Of Battery Filled Slots	4
Number Of Battery Free Slots	0
Battery Recharge Time	2.2 h
Number Of Battery Replacement Quantity	2
Additional Information	Configurable for 208 or 240 nominal output voltage
Battery Charger Power	869 W rated
Battery Power In Vah	1920 VAh runtime
Battery Life	3...5 year(s)

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Replacement Battery	APCRBC140  SRT192BP2US  SRT192RMBPUS  SURT192XLBP-IN 
---------------------	--

Battery Option	SURT192XLBP 1 3840 VAh SURT192XLBP 2 5760 VAh SURT192XLBP 3 7680 VAh SURT192XLBP 4 9600 VAh SURT192XLBP 5 11520 VAh SURT192XLBP 6 13440 VAh SURT192XLBP 7 15360 VAh SURT192XLBP 10 21120 VAh
----------------	---

Extended Runtime	1
------------------	---

General

Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

Physical

Colour	Black
Height	43.2 cm
Width	26.3 cm
Depth	73.6 cm
Net Weight	110.91 kg
Mounting Location	Front
Mounting Preference	Lower
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

Input

Network Frequency	50/60 Hz +/- 5 Hz auto-sensing
Number Of Input Connectors	1 hard wire 3-wire (2P + E)
Input Voltage Limits	160...280 V
Input Harmonic Distortion	Less than 7 % for full load

Output

Maximum Configurable Power In W	8000 W
Harmonic Distortion	Less than 3 %
Output Frequency	50/60 Hz +/- 3 Hz user adjustable +/- 0.1 Hz sync to mains
Crest Factor	3 : 1
Ups Type	Double conversion online
Wave Type	Sine wave

Bypass Type	Internal bypass (automatic and manual)
Efficiency	92 % (full load)
Maximum Configurable Power In Va	10000 VA

Conformance

Product Certifications	CSA FCC part 15 class A UL 1778
------------------------	---------------------------------------

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 % non-condensing
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	-15...45 °C
Storage Relative Humidity	0...95 % Non-condensing
Storage Altitude	0.00...15240.00 m
Acoustic Level	55 dBA
Heat Dissipation	2454 Btu/h
Ip Degree Of Protection	IP20

Communications & Management

Free Slots	0
Preinstalled Device	Network management card 2 with environmental monitoring
Control Panel	LED status display with load and battery bar-graphs and on line : on battery : replace battery : overload and bypass indicators
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency Power Off	Yes

Surge Protection and Filtering

Surge Energy Rate	1265 J
Noise Suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Package 1 Weight	129.09 kg
Package 1 Height	55.2 cm
Package 1 Width	59.7 cm
Package 1 Length	99.1 cm
Number Of Units In Package 3	2

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. **Green Premium** promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low- products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant
[EU RoHS Declaration](#)

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)