

Product data sheet

Specifications



APC Smart-UPS RT 5000VA, 230V,
no battery, rackmount w/kit, 3U, 8x
IEC 60320 C13 & 4x IEC Jumpers &
2x IEC 60320 C19 outlets

SURT5000UXICH

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	230 V
product or component type	Uninterruptible power supply (UPS)
Other Input Voltage	220 V 240 V
Main Output Voltage	230 V
Other Output Voltage	220 V 240 V
Rated power in W	3500 W
Rated power in VA	5000 VA
output connection type	8 IEC 60320 C13 4 IEC Jumpers 2 IEC 60320 C19
Number of rack unit	3U
Provided equipment	CD with software Smart UPS signalling RS-232 cable User manual

Batteries & Runtime

Run Time	View Runtime Graph
Battery type	External battery system
Number of battery filled slots	0
Number of battery free slots	2
Extended runtime	1

General

UPS type	Double conversion online
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Colour	Black
--------	-------

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Height	43.2 cm
Width	13 cm
Depth	69.85 cm
net weight	36.36 kg
mounting location	Front
Mounting preference	Lower
mounting mode	Rack-mounted with kit
Two post mountable	0
USB compatible	No

Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Number of input connectors	1 hard wire 3-wire
Input voltage limits	160...280 V

Output

Maximum configurable power in VA	5000 VA
Maximum configurable power in W	3500 W
Output frequency	50/60 Hz +/- 3 Hz user adjustable +/- 0.1 Hz sync to mains
Wave type	Sine wave
Efficiency	92 % (full load)
Harmonic distortion	Less than 3 %
Crest factor	3 : 1
Bypass type	Internal bypass (automatic and manual)
Additional information	Configurable for 220 : 230 or 240 nominal output voltage

Conformance

Product certifications	C-Tick CE GOST VDE
Standards	EN/IEC 62040-1:2019/A11:2021 EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.0000000000...15240.0000000000 m
Acoustic level	55 dBA
heat dissipation	1040 Btu/h

IP degree of protection	IP20
-------------------------	------

Communications & Management

Free slots	1
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency power off	Yes

Surge Protection and Filtering

Surge energy rate	480 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	34.7 cm
Package 1 Width	98 cm
Package 1 Length	60.3 cm
Package 1 Weight	45.45 kg

Contractual warranty

Warranty	2 years repair or replace, optional on-site warranties available, optional extended warranties available
----------	--

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

Environmental Disclosure [Product Environmental Profile](#)

Circularity Profile [End of Life Information](#)