

Product data sheet

Specifications



APC Smart-UPS RT 2200VA, 120V, 6x NEMA 5-15R outlets, w/network card

SURTA2200RML2U-NC

 **Discontinued on:** Jun 15, 2022

 **Discontinued**



Overview

Lead time Usually in Stock

Main

Main Input Voltage	120 V
Main Output Voltage	120 V
Rated power in W	1600 W
Rated power in VA	2200 VA
Input Connection Type	NEMA 5-20P
output connection type	6 NEMA 5-15R
Number of rack unit	2U
Cable length	1.8 m
Number of cables	1
Provided equipment	CD with software Documentation CD Rack mounting brackets Rack mounting support rails Smart UPS signalling RS-232 cable User manual

Batteries & Runtime

Run Time	View Runtime Graph 
Battery type	Lead-acid battery
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	1
Battery charger power	144 W rated
Battery life	3...5 year(s)
Replacement battery	RBC57 
Extended runtime	1

General

UPS type Double conversion online

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Colour	Black
Height	8.5 cm
Width	43.2 cm
Depth	55.9 cm
net weight	27.5 kg
mounting location	Front
Mounting preference	Lower
mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	Yes

Input

Network frequency	50/60 Hz +/- 5 Hz auto-sensing
Input voltage limits	90...150 V

Output

Maximum configurable power in VA	2200 VA
Maximum configurable power in W	1600 W
Output frequency	50/60 Hz +/- 3 Hz user adjustable +/- 0.1 Hz sync to mains
Wave type	Sine wave
Harmonic distortion	Less than 3 %
Crest factor	3 : 1
Bypass type	Built-in bypass

Conformance

Product certifications	BSMI CSA
------------------------	-------------

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-20...50 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.0000000000...15240.0000000000 m
Acoustic level	45 dBA
heat dissipation	587 Btu/h

IP degree of protection	IP20
-------------------------	------

Communications & Management

Free slots	1
Preinstalled device	Network management card 2 with environmental monitoring
Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm
Emergency power off	Yes

Surge Protection and Filtering

Surge energy rate	540 J
Noise suppression	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : meets UL 1449

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	26 cm
Package 1 Width	61 cm
Package 1 Length	73.7 cm
Package 1 Weight	31.234 kg

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back Transparency RoHS/REACH

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Certifications & Standards

Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant with Exemptions
Environmental Disclosure	Product Environmental Profile
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information