

Product datasheet

Specifications



APC Smart-UPS "VS" 420VA 230V

SUVS420I

Discontinued on: Jun 10, 2022

Discontinued

Overview

Lead Time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Rated Power In W	280 W
Rated Power In Va	420 VA
Input Connection Type	IEC 60320 C14
Output Connection Type	4 IEC 60320 C13
Number Of Rack Unit	0U
Number Of Cables	1
Battery Type	Lead-acid battery

Batteries & Runtime

Run Time	View Runtime Graph
Extended Runtime	0
Number Of Battery Filled Slots	0
Number Of Battery Free Slots	0
Battery Recharge Time	8 h
Number Of Battery Replacement Quantity	1
Battery Life	3...5 year(s)
Replacement Battery	RBC2
Battery Charger Power	10 W rated

General

Number Of Power Module Filled Slots	0
Number Of Power Module Free Slots	0
Redundant	No

Physical

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Mounting Location	Front
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Two Post Mountable	0
Usb Compatible	No

Output

Maximum Configurable Power In Va	420 VA
Maximum Configurable Power In W	280 W
Transfer Time	2 ms typical
Ups Type	Line interactive

Environmental

Operating Altitude	0...10000 ft
Ambient Air Temperature For Operation	0...40 °C
Ambient Air Temperature For Storage	-15...45 °C
Storage Altitude	0.00...15240.00 m
Relative Humidity	0...95 %
Storage Relative Humidity	0...95 %

Communications & Management

Free Slots	0
------------	---

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	0.01 cm
Package 1 Width	0.01 cm
Package 1 Length	0.01 cm
Package 1 Weight	10.433 kg

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------