

Product datasheet

Specifications



APC Smart-UPS VS 650VA 230V

SUVS650I

⚠ Discontinued on: Jun 10, 2022

⚠ Discontinued

Overview

Lead time	Usually in Stock
-----------	------------------

Main

Main Input Voltage	230 V
Main Output Voltage	230 V
Rated power in W	400 W
Rated power in VA	650 VA
Input Connection Type	IEC 60320 C14
output connection type	4 IEC 60320 C13
Number of rack unit	0U
Number of cables	1
Battery type	Lead-acid battery

Batteries & Runtime

Run Time	View Runtime Graph
Extended runtime	0
Number of battery filled slots	0
Number of battery free slots	0
Battery recharge time	14400 h
Number of battery replacement quantity	1
Battery life	3...5 year(s)
Replacement battery	RBC4

General

Number of power module filled slots	0
Number of power module free slots	0
Redundant	No

Physical

mounting location	Front
-------------------	-------

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Mounting preference	No preference
mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No

Output

Maximum configurable power in VA	650 VA
Maximum configurable power in W	400 W
Transfer time	2 ms typical
UPS type	Line interactive

Environmental

Operating altitude	0...10000 ft
Ambient air temperature for operation	0...40 °C
Ambient air temperature for storage	-15...45 °C
Storage altitude	0.0000000000...15240.0000000000 m
Relative humidity	0...95 %
Storage Relative Humidity	0...95 %

Communications & Management

Free slots	0
------------	---

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.01 cm
Package 1 Width	0.01 cm
Package 1 Length	0.01 cm
Package 1 Weight	12.247 kg

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------