

You are here: [Home](#) » [Products](#) » [Uninterruptible Power Supply \(UPS\)](#) » [Smart-UPS VT](#)

Smart-UPS VT

APC Smart-UPS VT 10kVA 208V w/1 Batt. Module Exp. to 2, Start-Up 5X8, Internal Maintenance Bypass

SUVT10KF1B2S

DISCONTINUED

Product Category

- Computer and Peripheral (5)
- Home UPS (2)
- Network and Server (3)
- Data Center and Facility 3 Phase
 - > Symmetra PX
 - > Symmetra MW
 - > **Smart-UPS VT**
 - > MGE Galaxy 3500
 - > MGE Galaxy 4000
 - > MGE Galaxy 5000
 - > MGE Galaxy PW
 - > MGE Galaxy 7000
 - > MGE Galaxy 6000
 - > MGE Galaxy 9000
 - > MGE EPS 7000
 - > MGE EPS 8000
 - > MGE Galaxy 300
 - > Power Generation Systems
- UPS Management (7)

[Return to Uninterruptible Power Supply \(UPS\)](#)



APC Smart-UPS VT, 8000 Watts / 10 kVA, Input 208V 3PH / Output 200V 3PH, 208V 3PH , Interface Port DB-9 RS-232, Smart-Slot

Includes: Battery modules ship installed, Bolt down brackets, CD with software, Installation guide, Power modules ship installed, Smart UPS signalling RS-232 cable, Start up included, User Manual, Web/SNMP Management Card



Be the first to [write a review](#)

[+ More Images](#)

Technical Specifications

Product Overview

Documentation

Options

Ratings and Reviews

Output

Output Power Capacity	8000 Watts / 10 kVA
Max Configurable Power	8000 Watts / 10 kVA
Nominal Output Voltage	200V 3PH,208V 3PH
Output Voltage Note	Configurable for 208 and 220V - 3 Phase
Efficiency at Full Load	93.0%
Output Voltage Distortion	Less than 5% at full load
Output Frequency (sync to mains)	57 - 63 Hz for 60 Hz nominal
Other Output Voltages	220
Crest Factor	Unlimited
Waveform Type	Sine wave
Output Connections	(1) Hard Wire 5-wire (3PH + N + G) (1) Screw Terminals
Bypass	Built-in Maintenance Bypass,Built-in Static Bypass

Input


Nominal Input Voltage	208V 3PH
Input Frequency	40 - 70 Hz (auto sensing)
Input Connections	Hard Wire 5-wire (3PH + N + G)
Input voltage range for main operations	165 - 240V
Other Input Voltages	220
Maximum Input Current	27A
Input Breaker Capacity	35.0 A

Batteries & Runtime

Battery Type	VRLA
Included Battery Modules	1
Available Battery Slots	1
Typical recharge time	5 hour(s)
Replacement Battery	SYBT4
RBC™ Quantity	1

Runtime Graph

Curve	Part Number(s)
A	SUVT10KF1B2S
B	SUVT10KF1B2S + (1)SYBT4
C	SUVT10KF1B2S + (1)SUVTBXR2B6S
D	SUVT10KF1B2S + (1)SUVTBXR6B6S
E	SUVT10KF1B2S + (2)SUVTBXR6B6S



Hover over the line on the graph above to view the runtime at any desired load

Curve fit to measured runtime data. All measurements taken with new, fully charged batteries, at typical environmental conditions, with no electrical input and balanced resistive load (PF = 1.0)

[View Enlarged Graph](#)[View Runtime Chart](#)

Communications & Management

Interface Port(s)	DB-9 RS-232,Smart-Slot
Pre-Installed SmartSlot™ Cards	AP9619
Control panel	Multi-function LCD status and control console
Audible Alarm	Audible and visible alarms prioritized by severity
Emergency Power Off (EPO)	Yes

Physical

Maximum Height	1499.00 mm
Maximum Width	356.00 mm
Maximum Depth	925.00 mm
Net Weight	305.00 KG
Shipping Weight	335.92 KG
Shipping Height	1643.00 mm
Shipping Width	650.00 mm
Shipping Depth	1062.00 mm
Color	Black
Units per Pallet	1.00

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-999.9 meters
Storage Temperature	-50 - 40 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-15000 meters
Audible noise at 1 meter from surface of unit	54.00 dBA
Online Thermal Dissipation	2047.00 BTU/hr
Protection Class	NEMA 1

Conformance

Regulatory Approvals	cUL Listed,ISO 14001,ISO 9001,UL 1778
Standard Warranty	1 year repair or replace,Start-Up Service