

Product data sheet

Specifications



APC Smart-UPS VT 10KVA 400V w/1 Batt Mod Exp to 2, Int Maint Bypass, Parallel Capable

SUVTP10KH1B2

! Discontinued - Service only

! Discontinued on: Dec 31, 2020

! To be end-of-service on: Dec 31, 2030

Overview

Lead Time Special Order - Call for Quoted Lead Times

Main

Main Input Voltage	400 V 3 phases
Other Input Voltage	380 V 415 V
Main Output Voltage	230 V 400 V 3 phases
Other Output Voltage	380 V 415 V
Rated Power In W	8000 W
Rated Power In Va	10000 VA
Output Connector Type	Hard wire 4-wire (3P + E) 1 Hard wire 5-wire (3P + N + E) 1
Connections - Terminals	1 screw terminals
Battery Type	VRLA
Provided Equipment	Battery modules ship installed CD with software Installation guide Power modules ship installed User manual Web/SNMP management card

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Number Of Battery Filled Slots	1
Number Of Battery Free Slots	1
Battery Recharge Time	5 h
Number Of Battery Replacement Quantity	1
Additional Information	Configurable for 380 : 400 or 415 V 3 Phase nominal output voltage
Battery Voltage	+/- 192 V (split battery referenced to neutral)
Discharge Battery Voltage	+/- 154 V
Battery Charger Power	502 W rated

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Battery Power In Vah	2513 VAh runtime
Battery Life	3...5 year(s)
Replacement Battery	SYBT4 
Battery Option	SYBT4 1 4983 VAh SUVTXR6B6S 1 17226 VAh SUVTBXR6B6S 2 32279 VAh SUVTBXR6B6S 3 47439 VAh SUVTBXR6B6S 4 62835 VAh
Extended Runtime	0

General

Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	No

Physical

Colour	Black
Height	149 cm
Width	35.3 cm
Depth	83.8 cm
Net Weight	305 kg
Mounting Location	Front
Mounting Preference	No preference
Mounting Mode	Not rack-mountable
Usb Compatible	No

Input

Network Frequency	40...70 Hz auto-sensing
Number Of Input Connectors	1 hard wire 5-wire (3P + N + E)
Input Voltage Limits	304...477 V
Maximum Input Current	14 A
Switching Current Capacity	20 A
Input Harmonic Distortion	Less than 5 % for full load
Load Power Factor	0.5 leading to 0.5 lagging
Input Power Factor At Full Load	0.98

Output

Maximum Configurable Power In W	8000 W
Harmonic Distortion	Less than 5 % at full load
Output Frequency	47...53 Hz for 50 Hz nominal sync to mains 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised
Crest Factor	Unlimited
Ups Type	Double conversion online
Wave Type	Sine wave

Output Voltage Tolerance	+/- 1% static and +/- 5% at 100% load step
Output Harmonic Distortion	< 2% for 0 to 100% linear load and < 5% for full non-linear load
Output Overload Operation	10 minutes at 125% and 60 seconds at 150%
Required Output Current Protection	20 A
Bypass Type	Built-in maintenance bypass Built-in static bypass
Efficiency	95.7 % (full load) 95.2 % (half load)
Maximum Output Current	16 A
Maximum Configurable Power In Va	10000 VA

Conformance

Standards	EN 50091-2 EN/IEC 62040-2 EN/IEC 62040-3 EN/IEC 62040-1-1 ISO 14001 ISO 9001
-----------	---

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 %
Operating Altitude	0...3333 ft
Ambient Air Temperature For Storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage Altitude	0.00...15240.00 m
Acoustic Level	54 dBA
Heat Dissipation	1501 Btu/h
Ip Degree Of Protection	IP20

Communications & Management

Free Slots	0
Preinstalled Device	Network management card with environmental monitoring
Control Panel	Multifunction LCD status and control console
Alarm	Audible and visible alarms : configurable delays
Emergency Power Off	Yes

Packing Units

Package 1 Height	164.3 cm
Package 1 Width	65 cm
Package 1 Length	106.2 cm
Package 1 Weight	335.91 kg
Number Of Units In Package 3	1

Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up
----------	---

Sustainability

Green Premium™ label label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. **Green Premium** promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low- products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

Eu Rohs Directive

Under investigation
