

Product data sheet

Specifications



APC Smart-UPS VT 30KVA 208V w/ 4 Batt Mod Exp to 4, Int Maint Bypass, Parallel Capable

SUVTP30KF4B4

! Discontinued

! Discontinued on: Dec 31, 2020

! End-of-service on: Oct 18, 2023

Overview

Lead time Usually Ships within 2 Weeks

Main

Main Input Voltage	208 V 3 phases
Other Input Voltage	220 V
Main Output Voltage	120 V 208 V 208 V 3 phases
Other Output Voltage	220 V
Rated power in W	24000 W
Rated power in VA	30000 VA
Output connector type	Hard wire 5-wire (3P + N + E) 1
Connections - terminals	1 screw terminals
Provided equipment	Battery modules ship installed CD with software Power modules ship installed User manual Web/SNMP management card Bolt down brackets Installation guide

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Battery type	Lead-acid battery
Number of battery filled slots	4
Number of battery free slots	0
Battery recharge time	5 h
Number of battery replacement quantity	4
Battery voltage	+/- 192 V (split battery referenced to neutral)
Discharge battery voltage	+/- 154 V
Battery overload operation	10 minutes at 125% and 60 seconds at 150%
Battery charger power	1965 W rated

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Battery life	3...5 year(s)
Replacement battery	SYBT4 
Extended runtime	1

General

UPS type	Double conversion online
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No

Physical

Colour	Black
Height	149.9 cm
Width	52.3 cm
Depth	83.8 cm
net weight	629.09 kg
mounting location	Front
Mounting preference	No preference
mounting mode	Not rack-mountable
USB compatible	No

Input

Network frequency	40...70 Hz
Number of input connectors	1 hard wire 5-wire (3P + N + E)
Input voltage limits	165...240 V
Maximum input current	80 A
Switching current capacity	125 A
Input harmonic distortion	Less than 5 % for full load
Input protection type	3-pole circuit breaker
Load power factor	0.5 leading to 0.5 lagging
Input Power Factor at Full Load	0.98

Output

Maximum configurable power in VA	30000 VA
Maximum configurable power in W	24000 W
Output frequency	57...63 Hz for 60 Hz nominal sync to mains 60 Hz +/- 0.1 % for 60 Hz nominal unsynchronised
Wave type	Sine wave
Output overload operation	10 minutes at 125% and 60 seconds at 150%
Efficiency	93 % (full load) 92.9 % (half load)
Harmonic distortion	Less than 5 % at full load

Maximum output current	92 A
Crest factor	Unlimited
Bypass type	Built-in maintenance bypass Built-in static bypass
Additional information	Configurable for 208 and 220V - 3 Phase

Conformance

Product certifications	cUL listed CE
------------------------	------------------

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...3333 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...15240.0000000000 m
Acoustic level	54 dBA
heat dissipation	6305 Btu/h
NEMA degree of protection	NEMA 1

Communications & Management

Free slots	0
Preinstalled device	Network management card with environmental monitoring
Emergency power off	Yes

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	164.3 cm
Package 1 Width	106.2 cm
Package 1 Length	65 cm
Package 1 Weight	660 kg

Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up
----------	---