

Product data sheet

Specifications



Symmetra PX 125kW Scalable to 500kW without MBP & Distribution-Parallel Capable, Japan

SY125K500JD

Overview

Presentation	A high-performance, 3-phase, modular, scalable, power protection solution with industry-leading efficiency, capacity, and performance for medium to large data centers and mission-critical environments. Multiple UPSs can be installed in parallel for ultra-efficient system redundancy or up to 2MW of power protection. Parallel installations with custom switchgear and installations using a 3rd-party maintenance bypass panel require the APC Symmetra PX250/500 Third Party Switchgear Kit for breaker monitoring and EPO functionality.
--------------	---

Lead time	Usually Ships within 6 Weeks
-----------	------------------------------

Main

Main Input Voltage	400 V 3 phases 415 V 3 phases
Other Input Voltage	380 V 480 V
Main Output Voltage	400 V 3 phases 415 V 3 phases
Other Output Voltage	380 V 480 V
Rated power in W	125000 W
Rated power in VA	125000 VA
Output connector type	Hard wire 4-wire (3P + E) 1 Hard wire 5-wire (3P + N + E) 1
Battery type	VRLA
Provided equipment	Assembly service Installation guide Network management card Start-up service User manual

Batteries & Runtime

Number of battery filled slots	8
Number of battery free slots	0
Battery recharge time	3 h
Number of battery replacement quantity	6
Battery overload operation	10 minutes at 125% and 60 seconds at 150%
Battery charger power	13778 W rated
Battery design life	5...8 year(s)
Extended runtime	1

General

Bypass voltage tolerance	+/- 10 % settable from +/- 4/6/8 and 10 %
Number of power module free slots	15
Number of power module filled slots	5
Redundant	Yes

Physical

Colour	Black
Height	199.1 cm
Width	255 cm
Depth	107 cm
Net weight	2734 kg
USB compatible	No

Input

Network frequency	40...70 Hz auto-sensing
Number of input connectors	1 hard wire 5-wire (3P + N + E)
Input voltage limits	340...460 V 400 V 353...477 V 415 V
Max short time withstand current	50 kA
Input harmonic distortion	Less than 5 % for full load
Input protection type	3-pole circuit breaker
Load power factor	0.5 leading to 0.5 lagging
Input Power Factor at Full Load	0.99

Output

Maximum configurable power in W	500000 W
Harmonic distortion	Less than 2 %
Output frequency	50 Hz sync to mains 60 Hz +/- 0.1 % for 60 Hz nominal unsynchronised 50 Hz +/- 0.1 % for 50 Hz nominal unsynchronised 60 Hz sync to mains
UPS type	Double conversion online
Wave type	Sine wave
Output voltage tolerance	+/- 1% static and +/- 5% at 100% load step
Output harmonic distortion	< 2% linear load and < 3% non-linear load
Output overload operation	10 minutes at 125% and 60 seconds at 150%
Bypass type	Built-in maintenance bypass Built-in static bypass
Efficiency	96.3 % (in battery operation)
Maximum configurable power in VA	500000 VA
Transfer time	2 ms typical

Conformance

Product certifications	BAJ cUL listed UL listed
Standards	CSA C22.2 No 107.3-05 EN/IEC 62040-1-1 EN/IEC 62040-2 EN/IEC 62040-3 UL 1778 UL 60950-1

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...3333 ft
Ambient air temperature for storage	-15...40 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m
Acoustic level	54 dBA
Heat dissipation	19427 Btu/h
NEMA degree of protection	NEMA 1
IP degree of protection	IP20

Communications & Management

Free slots	1
Preinstalled device	Network management card 2 with environmental monitoring, out of band access and Modbus
Control panel	Touch screen LCD user interface
Emergency power off	Optional

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	215 cm
Package 1 Width	127 cm
Package 1 Length	299 cm
Package 1 Weight	3036 kg

Offer Sustainability

EU RoHS Directive	Not compliant
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up
----------	---

Recommended replacement(s)