



Commercial status

This Product is Obsolete : DEC 20, 2023

⚠ This Product is Obsolete

Overview

Presentation	A modular, high-efficiency 3-phase UPS that is scalable up to 100kW. Suitable for use in small to medium data centers and high density zones.
Lead time	Usually Ships within 3 Weeks

Main

Main Input Voltage	208 V 3 phase
Output voltage	120 V 208 V 208 V 3 phase
Kw Rating	20000 W
Rated power in VA	20000 VA
Output connector type	Hard Wire 5-wire (3PH + N + G) 1
Provided equipment	Installation guide Network Management Card Start-Up Service User Manual

Batteries & Runtime

Extendable Run Time	0
---------------------	---

General

Number of power module free slots	9
Number of power module filled slots	1
Redundant	Yes

Physical

Color	Black
Height	79.17 In (201.1 cm)
Width	23.62 In (60 cm)
Depth	42.13 In (107 cm)
Net Weight	791.24 Lb(US) (358.9 kg)
USB compatible	No

Input

Input Frequency	40 - 70 Hz
Efficiency at full load	177...239 V 208 V
Maximum Input Current per Phase	332 A
Input Total Harmonic Distortion	Less than 5% for full load
Load power factor	0.5 leading to 0.5 lagging
Cos phi	0.99

Output

Max Configurable Power (Watts)	100000 W
Harmonic distortion	Less than 2%
Output Frequency (sync to mains)	57...63 Hz for 60 Hz nominal sync to mains 60 Hz +/- 0.1 % for 60 Hz nominal not synced 50 Hz +/- 0.1 % for 50 Hz nominal not synced
Topology	Double Conversion Online
Wave type	Sine wave
Output voltage tolerance	+/-1% static and +/- 5% at 100% load step
Output Voltage THD	< 2% for 0 to 100% linear load and < 6% for full non-linear load
Bypass type	Built-in Static Bypass
Maximum configurable power in VA	100000 VA
Transfer Time	2ms typical

Conformance

Standards	CSA C22.2 No.107.3-05 FCC Part 15 class A ISO 14001 ISO 9001 UL 1778
-----------	--

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 %
Operating altitude	0...3333 ft
Ambient Air Temperature for Storage	5...104 °F (-15...40 °C)
Storage Relative Humidity	0...95 %
Storage altitude	0...50000 Ft (0.00...15240.00 m)
Acoustic level	67 dBA
Heat dissipation	3292.6 Btu/H
NEMA degree of protection	NEMA 1

Communications & Management

Free slots	2
Pre-Installed SmartSlot® Cards	Network management card with CAN
Control panel	Multi-function LCD status and control console

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	84.25 In (214 cm)
Package 1 Width	47.64 In (121 cm)
Package 1 Length	33.39 In (84.8 cm)
Package 1 Weight	887.14 Lb(US) (402.4 kg)

Offer Sustainability

EU RoHS Directive	Under investigation
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up
----------	---

Product Life Status :	End of commercialisation
-----------------------	--------------------------