

Product data sheet

Specifications



Symmetra MW 1000kW frame, 400V

SYMF1000KH

⚠ Discontinued on: Feb 12, 2021

⚠ End-of-service on: Oct 18, 2023

⚠ Discontinued

Overview

Lead time Special Order - Call for Quoted Lead Times

Main

Main Input Voltage	400 V 3 phases
Other Input Voltage	380 V 415 V
Main Output Voltage	400 V 3 phases
Other Output Voltage	380 V 415 V
Rated power in W	1000000 W
Rated power in VA	1000000 VA
Output connector type	Hard wire 4-wire (3P + E) 1 Hard wire 5-wire (3P + N + E) 1 Hard wire 4-wire (3P + N) 1 Hard wire 4-wire (3P + PEN) 1
Number of cables	1
Battery type	External battery system
Provided equipment	Assembly service Start-up service User manual Installation guide

Batteries & Runtime

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph
Number of battery filled slots	0
Number of battery free slots	0
Additional information	Configurable for 380 : 400 or 415 V 3 Phase nominal output voltage
Battery power in VAh	0 VAh runtime
Extended runtime	1

General

Number of power module free slots	5
Number of power module filled slots	0

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Redundant	Yes
Physical	
Colour	Light grey (NCS 2703-G84Y)
Height	203.2 cm
Width	413.8 cm
Depth	106.7 cm
net weight	4196.82 kg
mounting location	Front
Mounting preference	No preference
mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No
Input	
Network frequency	50 Hz programmable +/- 0.5 / 1 / 2 / 4 / 6 / 8 %
Number of input connectors	1 hard wire 4-wire (3P + E) 1 hard wire 4-wire (3P + PEN) 1 hard wire 5-wire (3P + N + E)
Input voltage limits	323...437 V adjustable 380 V 340...460 V adjustable 400 V 357...477 V adjustable 415 V 323...437 V 380 V 340...460 V 400 V 353...477 V 415 V
Input Power Factor at Full Load	0.99
Output	
Maximum configurable power in W	1000000 W
Harmonic distortion	Less than 5 % at full load
Output frequency	50 Hz programmable +/- 0.5 / 1 / 2 / 4 / 6 / 8 % +/- 0.1 % for 50 Hz nominal 50 Hz +/- 0.1 % for 50 Hz nominal
Crest factor	Unlimited
UPS type	Delta conversion on-line
Wave type	Sine wave
Bypass type	External static bypass
Maximum output current	1838 A
Maximum configurable power in VA	1000000 VA
Conformance	
Product certifications	CE

Standards	EN 50091-1 EN 50091-2 EN 50091-3 EN 60950 EN/IEC 62040-3 FCC part 15 class A IEC 60950 ISO 14001 ISO 9001 VFI-SS-111
-----------	---

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...3333 ft
Ambient air temperature for storage	-50...40 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.0000000000...15240.0000000000 m
Acoustic level	75 dBA
heat dissipation	105600 Btu/h
IP degree of protection	IP20

Communications & Management

control panel	Touch screen LCD user interface
Emergency power off	Yes

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	223.5 cm
Package 1 Width	502.9 cm
Package 1 Length	128 cm
Package 1 Weight	4347.685 kg

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)



Energy Efficient Take-back

Resource performance

✓ Energy Efficient Product

✓ Take-Back Program Available

Well-being performance

✓ Reach Free Of Svhc

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)