

Product data sheet

Specifications



APC Symmetra RM 8kVA Scalable to 12kVA N+1 or 16kVA 208/240V

SYP8K12RMT

⚠ Discontinued on: Dec 31, 2005

⚠ End-of-service on: Dec 31, 2015

⚠ Discontinued - Service only

Overview

Lead Time Usually in Stock

Main

Main Input Voltage	208 V
Main Output Voltage	208 V
Rated Power In W	5600 W
Rated Power In Va	8000 VA
Nb Of Power Socket Outlets	6 NEMA L6-20R 3 NEMA L6-30R
Output Connector Type	Hard wire 3-wire (2P + E) 1
Number Of Rack Unit	15U
Number Of Cables	1
Battery Type	Lead-acid battery
Provided Equipment	CD with software Rack mounting brackets Rack mounting support rails User manual

Batteries & Runtime

Run Time	View Runtime Graph
Number Of Battery Filled Slots	2
Number Of Battery Free Slots	2
Battery Recharge Time	3 h
Additional Information	Configurable for 208 or 240 nominal output voltage
Battery Charger Power	537 W rated
Battery Power In Vah	1615 VAh runtime
Battery Life	3...5 year(s)
Battery Option	SYBT3 1 2423 VAh SYBT3 2 3230 VAh SYRMXR4B4 1 3904 VAh SYRMXR4B4 2 6193 VAh SYRMXR4B4 3 8482 VAh SYRMXR4B4 4 10771 VAh SYRMXR4B4 5 13060 VAh SYRMXR4B4 6 15349 VAh
Extended Runtime	1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

General

Number Of Power Module	4
Number Preinstalled Power Module	2
Number Of Power Module Free Slots	0
Number Of Power Module Filled Slots	0
Redundant	Yes

Physical

Colour	Black
Height	66.7 cm
Width	48.3 cm
Depth	73.7 cm
Net Weight	162.73 kg
Mounting Location	Front
Mounting Preference	Lower
Mounting Mode	Rack-mounted
Usb Compatible	No

Input

Network Frequency	50/60 Hz +/- 5 Hz manual switch
Number Of Input Connectors	1 hard wire 3-wire (2P + E)
Input Voltage Limits	155...276 V
Input Power Factor At Full Load	0.98

Output

Maximum Configurable Power In W	8400 W
Harmonic Distortion	Less than 5 % at full load
Output Frequency	57...63 Hz for 60 Hz nominal sync to mains 60 Hz +/- 0.1 % for 60 Hz nominal unsynchronised
Crest Factor	Up to 5 : 1
Ups Type	Double conversion online
Wave Type	Sine wave
Bypass Type	Internal bypass (automatic and manual)
Efficiency	91 % (full load)
Maximum Configurable Power In Va	12000 VA

Conformance

Product Certifications	CSA
Standards	FCC part 15 class A UL 1778

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 %
Operating Altitude	0...10000 ft
Ambient Air Temperature For Storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage Altitude	0.00...15240.00 m
Acoustic Level	62 dBA
Heat Dissipation	1889 Btu/h

Communications & Management

Free Slots	1
Preinstalled Device	Network management card with environmental monitoring
Control Panel	Multifunction LCD status and control console
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency Power Off	Yes

Packing Units

Package 1 Weight	180.91 kg
------------------	-----------

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

Sustainability

Green Premium™ label label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. **Green Premium** promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low- products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

Eu Rohs Directive

Under investigation
