

Product Category

- Computer and Peripheral (7)
- Home UPS (1)
- Network and Server
 - > Smart-UPS
 - > Smart-UPS On-Line
 - > Smart-UPS BR
 - > Symmetra
- Data Center and Facility 3 Phase (14)
- Special Applications (5)
- UPS Management (7)
- UPS Replacement Batteries (2)



Return to Uninterruptible Power Supply (UPS)

Symmetra Power Module

Symmetra PX 10kW Power Module, 208V, High Efficiency



More Images

APC Symmetra Power Module, 10 kW / 10 kVA, Input 208V, 208V 3PH / Output 208V, 208V 3PH, Extended runtime model

Includes: Installation guide

Standard Lead Time: Usually Ships within 2 Weeks



Be the first to write a review

SYPM10KF2



Email Technical Specifications



Printer Friendly



Locate a Partner



Technical Specifications

Product Overview

Documentation

Ratings and Reviews

Output

Output Power Capacity	10 kW / 10 kVA
Max Configurable Power	10 kW / 10 kVA
Nominal Output Voltage	208V, 208V 3PH
Efficiency at Full Load	94.7%
Output Voltage Distortion	Less than 5% at full load
Output Frequency (sync to mains)	57 - 63 Hz for 60 Hz nominal
Crest Factor	Unlimited
Topology	Double Conversion Online
Waveform Type	Sine wave

Input

Nominal Input Voltage	208V, 208V 3PH
Input Frequency	60 Hz +/- 3 Hz
Input voltage range for main operations	177 - 239 (208V)V

Communications & Management

Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Emergency Power Off (EPO)	--

Physical

Maximum Height	132.00 mm
Maximum Width	483.00 mm
Maximum Depth	700.00 mm
Net Weight	25.05 KG
Shipping Weight	28.05 KG
Shipping Height	225.00 mm
Shipping Width	595.00 mm
Shipping Depth	795.00 mm
Color	Black

Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95%
Operating Elevation	0-999.9 meters
Storage Temperature	-15 - 40 °C
Storage Relative Humidity	0 - 95%
Storage Elevation	0-4500 meters
Audible noise at 1 meter from surface of unit	64.00 dBA
Online Thermal Dissipation	2970.00 BTU/hr

Conformance

Regulatory Approvals	cUL Listed, FCC Part 15 Class A, ISO 14001, ISO 9001, UL 60950, UL Listed
Standard Warranty	1 year repair or replace

Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains No SVHCs