

Main

Range of Product	Altivar
Product or Component Type	Encoder interface module
Range Compatibility	Altivar&NbspProcess ATV900 Altivar Process Modular Altivar Machine ATV340
Encoder type	High threshold logic (HTL)
[Us] rated supply voltage	12 V DC 15 V DC 24 V DC

Complementary

Maximum supply current	0.2 A 12 V DC	
	0.175 A 15 V DC	
	0.1 A 24 V DC	
Protection Type	Short-circuit protection	
	Overload protection	
Maximum cable distance between devices	1640.42 ft (500 m)	
Maximum operating frequency	300 kHz	
Input signal	Push-pull differential A/AB/B	
	Push-pull single ended AB	
	Push-pull single ended A	
	Open collector differential A/AB/B	
	Open collector PNP AB	
	Open collector NPN AB	
	Open collector PNP A	
	Open collector NPN A	
Connector type	1 removable spring connector	
Net Weight	0.33 lb(US) (0.15 kg)	

Ordering and shipping details

Category	22209-ATV650
Discount Schedule	CP4E
GTIN	3606481211491
Returnability	Yes
Country of origin	ID

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.64 in (6.7 cm)	
Package 1 Width	5.04 in (12.8 cm)	
Package 1 Length	7.48 in (19.0 cm)	
Package 1 Weight	5.08 oz (144.0 g)	
Unit Type of Package 2	S03	
Number of Units in Package 2	16	
Package 2 Height	11.81 in (30.0 cm)	
Package 2 Width	11.81 in (30.0 cm)	

Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	6.73 lb(US) (3.052 kg)
Offer Sustainability	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEN RoHS
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₽¥Yes