

Switch Mode Power Supply -ATX12V v2.3- SS-XXXET Active PFC



www.seasonic.com



Features:

- Specification compliance: ATX12V v2.3
- Support the latest Intel & AMD Socket
- PCI Express & Serial ATA ready
- Double forward converter circuit
- High efficiency and reliability
- Low ripple & noise
- Super low noise fan control
- Short circuit protection on all outputs
- Over voltage protection & Over power protection
- 100% hi-pot test
- 100% burn in, high temperature cycled on/off

DC outputs:

Model	DC Outputs					Total power	Input type	
	+3.3V	+5V	+12V Combined	-12V	+5Vsb		Full range/Fixed 220V	
SS-600ET Active PFC	24A	24A	46A	0.8A	2.5A	600W	Yes	Yes
	130W ¹		552W	9.6W	12.5W			
SS-500ET Active PFC	24A	24A	34A	0.8A	2.5A	500W	Yes	Yes
	130W ¹		408W	9.6W	12.5W			
SS-400ET Active PFC	20A	20A	30A	0.8A	2.5A	400W	Yes	Yes
	130W ¹		360W	9.6W	12.5W			
SS-350ET Active PFC	20A	20A	27A	0.8A	2.5A	350W	Yes	Yes
	130W ¹		324W	9.6W	12.5W			
SS-300ET Active PFC	18A	20A	24A	0.8A	2.5A	300W	Yes	Yes
	120W ¹		288W	9.6W	12.5W			

Remarks: 1. Combined +3.3VDC & +5VDC maximum power

Electrical Specifications:

- Input frequency: 47/63 Hz
- Inrush current, cold start: 100A max.
- Efficiency: at normal input voltage $\geq 82\%$
- Line regulation: $\pm 1\%$ typical
- Load regulation: $\pm 5\%$ typical
- Cross regulation: $\pm 5\%$ typical
- Ripple / noise: 1%
- MTBF, full load @ 25°C amb. Excluding the DC fan: >100k hrs
- Power Factor Correction: 99% typical

Safety: CUL, TUV, CB, CCC

EMC: CE, FCC, C-tick

Dimension: L150 x W140 x H86mm
(5.9" x 5.5" x 3.4")

Connectors:

Main Power (24/20P) x 1
ATX12V (4P) x 1
ATX12V (8P/4P)x 1(500/580W)
Peripherals: SATA, HDD, FDD

Sea Sonic Electronics Co., Ltd.
www.seasonic.com
sales@seasonic.com.tw
Tel: +886 2 2659 0338
Fax: +886 2 2659 0530

Seasonic Electronics Inc.
www.seasonicusa.com
usa@seasonic.com
Tel: +1 626 969 9966
Fax: +1 626 969 9986

Sea Sonic Europe B.V.
europe@seasonic.com
Tel: +31 (0)10-2262131
Fax: +31 (0)10-2519947

Specification may change without prior notice

