

Metered C-12H 20-30A/16-32A 208-240V/230V (12) C13

1U, (12) outlets, (12) C13, (1) C20/L6-30P/60309 inlet, fused

[Contact Me](#)



(//cdn1.servertech.com/assets/images/images/1165/original/C-12H2-C20M_CMYK_black.jpg?1326171953)

Product Image Zoom: Mouse over the product image to view the image in more detail.

[Description](#)

[Specifications](#)

[Drawings](#)

[Documents](#)

[Support](#)

[Global Approvals](#)

Specifications

Sentry CDU Specifications

Available

Item #	Input Voltages	Rated Amperage	Available Input Cord	Outlets	Dimensions (L x W x D)
C-12H					
C-12H2-C20M	208-240 V 50/60Hz	20A	IEC 60320/C20 Power Inlet	(12) IEC 60320/C13	17.0 x 1.75 x 5.0 in. (432 x 44.4 x 127 mm)
C-12H2-L30M	208-240 V 50/60Hz	30A	NEMA L6-30P Cordset, 10 ft (3m)	(12) IEC 60320/C13	17.0 x 1.75 x 5.0 in. (432 x 44.4 x 127 mm)
C-12HE-C20M	230V 50/60Hz	16A	IEC 60320/C20 Power Inlet	(12) IEC 60320/C13	17.0 x 1.75 x 5.0 in. (432 x 44.4 x 127 mm)
C-12HE-P32M	230V 50/60Hz	32A	IEC 60309 Cordset, 10 ft (3m)	(12) IEC 60320/C13	17.0 x 1.75 x 5.0 in. (432 x 44.4 x 127 mm)

Power Cord Options

- > PTCORD-1 IEC 60320/C19 - NEMA L6-20P (20A Twist-Lock) 10'
- > PTCORD-2 IEC 60320/C19 - Schuko 10'
- > PTCORD-3 IEC 60320/C19 - IEC 60309 (BS4343, CEE17) 16/20A Blue (UK Commando) 10'
- > PTCORD-4 IEC 60320/C19 - BS1363 13A (UK) 10'
- > PT-ADP-C19 Cable mount IEC 60320/C19 Connector

Additional Features and Specifications

Standards

- > cTUVus ? UL 60950-1:2003
- > CAN/CSA 22.2 No. 60950-1:2003
- > TUVGS ? EN 60950-1:2001
- > FCC Class A, Part 15
- > CE
- > EMC-EN 55022 Class A, EN 55024

Branch Circuit Protection

- > Compliant to UL 60950-1

1040 Sandhill Drive, Reno, Nevada 89521 1-800-835-1515 sales@servertech.com

Copyright 2015 Server Technology