



205 WATT

NEXT GENERATION. BREAKTHROUGH PERFORMANCE.

MULTI-CRYSTAL SILICON PHOTOVOLTAIC MODULE WITH 205W MAXIMUM POWER

This poly-crystalline 205 watt module features 12.6% module efficiency for an outstanding balance of size and weight to power and performance. Using breakthrough technology perfected by Sharp's 45 years of research and development, these modules use a textured cell surface to reduce reflection of sunlight, and BSF (Black Surface Field) structure to improve conversion efficiency. An anti-reflective coating provides a uniform blue color and increases the absorption of light. Common applications include office buildings, cabins, solar power stations, solar villages, radio relay stations, beacons, traffic lights and security systems. Ideal for grid-connected systems and designed to withstand rigorous operating conditions, Sharp's ND-205U1 modules offer maximum power output per square foot of solar array.



Solder-coated grid results in high fill factor performance under low light conditions.



Sharp multi-purpose modules offer industry-leading performance for a variety of applications.

FEATURES

- High-power module (205W) using 155mm square multi-crystal silicon solar cells with 12.6% module conversion efficiency
- Bypass diodes minimize the power drop caused by shade
- Textured cell surface to reduce the reflected sunlight and BSF (Black Surface Field) structure to improve cell conversion efficiency
- White tempered glass, EVA resin, and a weatherproof film, plus aluminum frame for extended outdoor use
- UL Listings: UL1703, cUL
- Sharp modules are manufactured in ISO 9001 certified facilities
- 25-year limited warranty on power output (see dealer for details)

ELECTRICAL CHARACTERISTICS

Cell	Poly-crystalline silicon
No. of Cells and Connections	60 in series
Open Circuit Voltage (Voc)*	36.3V
Maximum Power Voltage (Vpm)*	28.9V
Short Circuit Current (Isc)	7.91A
Maximum Power Current (Ipm)	7.1A
Maximum Power (Pmax)*	205W (+10% / -5%)
Module Efficiency Maximum Power (η_m)	12.6%
Maximum System Voltage	600VDC
Series Fuse Rating	15A
Type of Output Terminal	Cable with MC Connector

MECHANICAL CHARACTERISTICS


Dimensions (LxWxD)	64.6" x 39.1" x 1.8" / 1640mm x 994mm x 46mm
Weight (lbs/kg)	46.3lbs / 21kg
Size of Carton	68.3" x 43.2" x 4.5" / 1735mm x 1097mm x 114mm
Carton Quantity	2 pcs per carton
Pallet Quantity	28 pcs per pallet
Loading Capacity (48 ft container)	448 pcs (16 pallets)
Loading Capacity (53 ft container)	476 pcs (17 pallets)

ABSOLUTE MAXIMUM RATINGS


Operating Temperature (min to max, °F/°C)	-40 to 194°F / -40 to +90°C
Storage Temperature (min to max, °F/°C)	-40 to 194°F / -40 to +90°C

*(STC) Standard Test Conditions: 25°C, 1 kW/m², AM 1.5

IV CURVES



DIMENSIONS



Specifications and design are subject to change without notice.

In the absence of confirmation by product manuals, Sharp takes no responsibility for any defects that may occur in equipment using any Sharp devices. Contact Sharp to obtain the latest product manuals before using any Sharp device.

