



SITOP PSU100S/1AC/12VDC/14A

SITOP PSU100S 12 V/14 A stabilized power supply input: 120/230 V AC output: 12 V DC/14 A *Ex approval no longer available*

Input	
type of the power supply network	1-phase AC
supply voltage at AC	
• initial value	Automatic range selection
supply voltage	
• 1 at AC rated value	120 V
• 2 at AC rated value	230 V
input voltage	
• 1 at AC	85 ... 132 V
• 2 at AC	170 ... 264 V
design of input wide range input	No
overvoltage overload capability	2.3 × Vin rated, 1.3 ms
operating condition of the mains buffering	at Vin = 93/187 V
buffering time for rated value of the output current in the event of power failure minimum	20 ms
operating condition of the mains buffering	at Vin = 93/187 V
line frequency	
• 1 rated value	50 Hz
• 2 rated value	60 Hz
line frequency	47 ... 63 Hz
input current	
• at rated input voltage 120 V	3.24 A
• at rated input voltage 230 V	1.41 A
current limitation of inrush current at 25 °C maximum	60 A
fuse protection type	T 6.3 A/250 V (not accessible)
• in the feeder	Recommended miniature circuit breaker: from 10 A characteristic C
Output	
voltage curve at output	Controlled, isolated DC voltage
output voltage at DC rated value	12 V
output voltage	
• at output 1 at DC rated value	12 V
relative overall tolerance of the voltage	3 %
relative control precision of the output voltage	
• on slow fluctuation of input voltage	0.1 %
• on slow fluctuation of ohm loading	1 %
residual ripple	
• maximum	150 mV
• typical	20 mV
voltage peak	
• maximum	240 mV

• typical	100 mV
adjustable output voltage	11.5 ... 15.5 V
product function output voltage adjustable	Yes
type of output voltage setting	via potentiometer
display version for normal operation	Green LED for 12 V OK
type of signal at output	Relay contact (NO contact, rating 60 V DC/ 0.3 A) for 12 V OK
behavior of the output voltage when switching on	Overshoot of Vout < 3 %
response delay maximum	0.3 s
voltage increase time of the output voltage	
• typical	10 ms
output current	
• rated value	14 A
• rated range	0 ... 14 A; +50 ... +70 °C: Derating 3.5%/K
supplied active power typical	168 W
short-term overload current	
• on short-circuiting during the start-up typical	40 A
• at short-circuit during operation typical	40 A
duration of overloading capability for excess current	
• on short-circuiting during the start-up	800 ms
• at short-circuit during operation	800 ms
product feature	
• bridging of equipment	Yes
number of parallel-switched equipment resources for increasing the power	2
Efficiency	
efficiency in percent	87 %
power loss [W]	
• at rated output voltage for rated value of the output current typical	24 W
Closed-loop control	
relative control precision of the output voltage at load step of resistive load 10/90/10 % typical	5 %
setting time	
• load step 10 to 90% typical	1 ms
• load step 90 to 10% typical	1 ms
Protection and monitoring	
design of the overvoltage protection	< 20 V
response value current limitation	14 ... 16.4 A
property of the output short-circuit proof	Yes
design of short-circuit protection	Constant current characteristic
enduring short circuit current RMS value	
• typical	16.4 A
overcurrent overload capability in normal operation	overload capability 150 % Iout rated up to 5 s/min
display version for overload and short circuit	-
Safety	
galvanic isolation between input and output	Yes
galvanic isolation	Safety extra-low output voltage Uout acc. to EN 60950-1 and EN 50178
operating resource protection class	Class I
leakage current	
• maximum	3.5 mA
• typical	0.8 mA
protection class IP	IP20
Approvals	
certificate of suitability	
• CE marking	Yes
• UL approval	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (CSA C22.2 No. 60950-1, UL 60950-1)
• CSA approval	Yes; cULus-Listed (UL 508, CSA C22.2 No. 107.1), File E197259; cCSAus (CSA C22.2 No. 60950-1, UL 60950-1)
• cCSAus, Class 1, Division 2	No
• ATEX	No
certificate of suitability	

<ul style="list-style-type: none"> • IECEx • NEC Class 2 • ULhazloc approval • FM registration 	No
	No
	No
	No
type of certification CB-certificate	Yes
certificate of suitability	
<ul style="list-style-type: none"> • EAC approval 	Yes
certificate of suitability shipbuilding approval	Yes
shipbuilding approval	DNV GL
Marine classification association	
<ul style="list-style-type: none"> • American Bureau of Shipping Europe Ltd. (ABS) • French marine classification society (BV) • DNV GL • Lloyds Register of Shipping (LRS) • Nippon Kaiji Kyokai (NK) 	No
	No
	Yes
	No
	No
EMC	
standard	
<ul style="list-style-type: none"> • for emitted interference • for mains harmonics limitation • for interference immunity 	EN 55022 Class B
	EN 61000-3-2
	EN 61000-6-2
environmental conditions	
ambient temperature	
<ul style="list-style-type: none"> • during operation • during transport • during storage 	-25 ... +70 °C; with natural convection
	-40 ... +85 °C
	-40 ... +85 °C
environmental category according to IEC 60721	Climate class 3K3, 5 ... 95% no condensation
Mechanics	
type of electrical connection	screw-type terminals
<ul style="list-style-type: none"> • at input • at output • for auxiliary contacts • for signaling contact 	L, N, PE: 1 screw terminal each for 0.5 ... 2.5 mm ² single-core/finely stranded
	+, -: 2 screw terminals each for 0.5 ... 2.5 mm ²
	Alarm signals: 2 screw terminals for 0.5 ... 2.5 mm ²
	2 screw terminals for 0.5 ... 2.5 mm ²
width of the enclosure	70 mm
height of the enclosure	125 mm
depth of the enclosure	120 mm
required spacing	
<ul style="list-style-type: none"> • top • bottom • left • right 	50 mm
	50 mm
	0 mm
	0 mm
net weight	0.7 kg
product feature of the enclosure housing can be lined up	Yes
fastening method	Snaps onto DIN rail EN 60715 35x7.5/15
MTBF at 40 °C	1 614 510 h
other information	Specifications at rated input voltage and ambient temperature +25 °C (unless otherwise specified)

